ENGINE POWERED ARTICULATING BOOM LIFTS **AB15J (AB480J)**

Compliant with CE/AS/CSA/EAC standards

PRODUCT HIGHLIGHTS

Suitable for Narrow Spaces

Narrow width with zero tail sweep

Operating Efficiency

The working platform can be lifted and lowered to any position without need to operate the secondary arm

Reliable

The simple linkage mechanism design and hydraulical leveling are reliable during operation

Precision Performance

3 joysticks with variable proportional control, accuracy in reaching the operation target



	Standard Features	
Oscillating function	7-in display screen	4WD×2WS
Proportional control with 3 joysticks	Automotive-grade sleeves for all pipes	4-wheel brake
Hydraulic platform leveling	Telematics-ready connector	Weighing system
Tilt protection system	Max tilt rating to 5°	Emergency stop system
Flashing beacon	Horn & buzzer	Emergency lowering system
Footswitch	1.83m(6') platform	Fault diagnosis system
Foam-filled tires	Manual storage box	AC power to platform
	Options & Accessories	
Foam-filled non-marking tires	Solid tires/Solid non-marking tires	1.45m (4'9") platform
Platform work light	Secondary guarding device	Overhead anti-collision device
Glazier kit(For platform with swinging gate)	Half mesh (For platform with swinging gate)	



PARTNERS IN ACCESS™

SINOBOOM.COM | SALES@SINOBOOM.COM NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600