





POWER YOU NEED, PRICE YOU WANT.

Three speed versatility and power reduces carpet drying times by up to 50%.

Power you need without breaking the bank.

Rely on the AirMover 3 and WindHandler 3 as your air blowers of choice. If you have wet floors or carpet, rely on the AirMover 3 to dry your facility up to 50 percent faster so you can resume to business-as-usual sooner. This economical unit features three speeds as well as three different vertical standing positions so you can direct air anywhere you need to. The powerful 3,000 cfm air movement promotes rapid drying in no time. Enjoy the convenience that the WindHandler 3 offers in this easily transportable three speed AirMover. Time is king in the cleaning industry. If you have wet hard floors or carpet, rely on the WindHandler 3 to dry your facility up to 50 percent faster so you can resume to business-as-usual sooner. This unit features transport wheels and an upright handle for easy transport from job to job. The powerful 3,000 cfm air movement promotes rapid drying in no time.



AirMover 3 Meets your needs

- Three speeds of air movement for every type of job
- Maximum air movement of 3,000 cfm for rapid drying of carped and hard floors
- Sturdy four point motor mount to withstand heavy use and rough handling
- Built-in carpet clip for flood restoration jobs
- Three different three standing positions to allow air to be directed in any angle

WindHandler 3 Meets your needs

- Upright handle and transport wheels for added safety and convenience
- Three speeds of air movement for every type of job
- Maximum air movement of 3,000 cfm for rapid drying of carped and hard floors
- Sturdy four point motor mount to withstand heavy use and rough handling
- Built-in carpet clip for flood restoration jobs

Technical Specifications and Order Numbers.

1.004-027.0

AirMover 3, three speed AirMover

1.004-015.0 Windhandler 3, three-speed commercial air blower with upright handle

| | | AIRMOVER 3 | WINDHANDLER 3 | |
|----------------------------|-----|-----------------|------------------|--|
| TECHNICAL SPECIFICATIONS | | | | |
| Motor | hp | 0.5 | 0.5 | |
| Fan wheel | in | 9.6 x 9.1 | 9.6 x 9.1 | |
| Speed (high/medium/low) | rpm | 1600/1350/1050 | 1600/1350/1050 | |
| Air flow (high/medium/low) | cfm | 3000/2500/2000 | 3000/2500/2000 | |
| Power cord | ft | 25 | 25 | |
| Electrical system | | 120 V AC, 60 Hz | 120 V AC, 60 Hz | |
| Weight | lbs | 33.5 | 39 | |
| Dimensions (L x W x H) | in | 20 x 16 x 18.8 | 22.8 x 16 x 21.5 | |

| 2 |
|---|
| - |

Please contact us for more information:

North America

4555 Airport Way Denver, CO 80239 U.S.A.

Phone +1 800 444-7654 Fax +1 866 271-0520

Canada

6535 Millcreek Drive Unit 67 Mississauga, ON L5N 2M2 Canada Phone +1 905 672-8233 Fax +1 905 672-3155

www.windsorkarchergroup.com