

 SHARE

Compact Track Loaders / T870 Compact Track Loader

Specifications & Options

	Standard	Optional	Not Applicable	Units	US
Bobcat T870					
Engine					
Emissions Tier (EPA)				Tier 4	
Engine Cooling				Liquid	
Engine Fuel				Diesel	
Horsepower				100 hp	
Turbocharged Engine					
Performance					
Rated Operating Capacity (SAE)				3,650 lb	
Operating Capacity (50% of Tip)				5215 lb	
Tipping Load				10430 lb	
Operating Weight				12925 lb	
Travel Speed				7.2 mph	
Travel Speed (2-speed option)				11.4 mph	
Ground Pressure (Rubber)				4.8 psi	
Capacities					
Fuel Tank				32.6 gal	
Hydraulic System					
System Relief @ Quick Couplers				3,500 psi	
Auxiliary Std Flow				23 gal/min	
Auxiliary High Flow				36.6 gal/min	

Dimension

Length	153.9 in
Length without Attachment	119.3 in
Length with Standard Bucket	153.9 in
Width	82.8 in
Width (with bucket)	84.8 in
Height	83.6 in
Height with Operator Cab	83.6 in
Height to Bucket Hinge Pin	144 in
Reach @ Maximum Height	36.5 in
Turning Radius	99 in
Length of track on ground	70.2 in
Track Width	17.7 in

Features

Joystick Control
Air Conditioning
Backup Alarm
BICS System (Interlock)
Cab Heater
Operating Lights
Suspension Seat
Two Speed Travel
Deluxe Instrumentation
Engine Shutdown
Hydraulic Bucket Positioning
High Flow Option
Auxiliary Hydraulics
Bob-Tach Attachment System
Power Bob-Tach
ACS (Switchable Controls)
Ride Control
Horn

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.