

BID SPECIFICATIONS

BOBCAT 60" SWEEPER

REQUIRED FEATURES

- Attachment will have a minimum sweep width of 60".
- Debris will be collected in a bucket that can be dumped when full.
- The bucket will utilize a reversible and replaceable, bolt-on cutting edge for scraping mud.
- The attachment will sweep with either forward or reverse loader travel.
- A gutter brush, with metal bristles, will be available as an option and will reach 26" ahead of the sweeper and 14" to the side of the sweeper.
- The gutter brush can be raised and stored vertically when not in use.
- Replaceable polypropylene sections will be used for bristles; steel sections will be available.
- An optional water kit must be available for dust control.

SPECIFICATIONS

Operating Weight.....	758 lbs. (344 kg)
Sweep Width.....	60" (1524 mm)
Overall Attachment Width.....	66.2" (1681 mm)
Bucket Capacity	12.0 ft ³ (0.34 m ³)
Broom Diameter.....	21.4" (545 mm)
Bristle Sections	30
Bristle Material	Polypropylene (steel available)
Travel	Forward/Reverse

MOUNTING

- The sweeper will be easily attached by means of hydraulic couplers and Bob-Tach™ mounting frame.
- Sweeper will not hinder the standard lift arm actions of the loader.
- The hydraulic supply lines for the sweeper will be routed through a hose guide location on the loader lift arm.

ATTACHMENT CONTROL

- Activation/deactivation and reversal of the sweeper rotation must be fingertip controlled from the operator seat without requiring operator to remove his/her hands from the loader steering levers.

SAFETY

- Entry and exit steps must be provided.
- Operation and safety decals must be displayed on the sweeper attachment.