€ SHARE

Attachments / Bucket, Rock - Loaders **Specifications**

Units US

| | Bucket, Rock - 62" | Bucket, Rock - 68" | Bucket, Rock - 74" | Bucket, Rock - 82" |
|---------------------|--------------------|--------------------|--------------------|--------------------|
| General | | | | |
| Operating Weight | 570 lb | 619 lb | 652 lb | 700 lb |
| Length | 43.6 in | 43.6 in | 43.6 in | 43.6 in |
| Width | 61.9 in | 68.6 in | 75.4 in | 82.1 in |
| Height | 20.8 in | 20.8 in | 20.8 in | 20.8 in |
| Tines | 17 | 19 | 21 | 23 |
| Tine Thickness | 0.4 in | 0.4 in | 0.4 in | 0.4 in |
| | | | | |
| Bucket Specs | | | | |
| ISO Heaped Capacity | n/a | n/a | n/a | n/a |
| ISO Struck Capacity | n/a | n/a | n/a | n/a |
| Predrilled For | n/a | n/a | n/a | n/a |

Compatible Carriers

Skid-Steer Loaders

Bobcat A770

Bobcat S450

Bobcat S550

Bobcat S570

Bobcat S590

Bobcat S630

Bobcat S630

Bobcat S740

Bobcat S770

Bobcat S770

Bobcat S770

Compact Track Loaders