



Make
Model

CASE
850 M LGP

CATERPILLAR
D 5 K 2 LGP

ENGINE		
Engine make / model	FPT F4HFE413P	Caterpillar C4.4 ACERT
Emission Rating	Interim Tier 4	Interim Tier 4
Net Power - hp (kW)	112 (84)	104 (77.6)
Gross Power - hp (kW)	120 (90)	not published
Rated RPM - rpm	2220	2200
Torque Output - lbf / ft (Nm)	not published	not published
Displacement - Inches ³ ; (ltr)	275 (4.5)	269 (4.4)
POWER TRAIN		
Transmission Type	Hydrostatic	Hydrostatic
Max Speed Fwd - mph (kph)	5.2 (8.4)	5.6 (9)
Max Speed Rev - mph (kph)	5.2 (8.4)	6.2 (10)
Drawbar Pull at Stall - lbf (kN)	42813 (190.4)	37093.4 (165)
Differential Steering	No	No
Steering Clutch/Brakes	No	No
UNDERCARRIAGE		
Shoe Width - inches (mm)	28 (711)	26 (660)
No. of Shoes	40	40
No. of Upper Rollers	1	1
No. of Bottom Rollers	7	7
Track on Ground - ft/in (mm)	7 ft 9 in (2350)	7 ft 7 in (2310)
PERFORMANCE		
Main Pump Type	Variable Displacement Piston	Variable Displacement Piston
Pump Flow - gallons (US) / min (lt/min)	20.3 (78.8)	19.4 (73.5)
Blade Type	PAT	VPAT
Blade Capacity - yd ³ ; (m ³);	2.62 (2)	3.06 (2.34)
Blade Width - ft/in (mm)	10 ft 4 in (3150)	10 ft 7 in (3220)
Length w/Dozer - ft/in (mm)	14 ft 5 in (4394)	14 ft 2 in (4309)
Height to Top of Cab - ft/in (mm)	9 ft 1 in (2769)	8 ft 11 in (2722)
Fuel Tank - gallons (US) (ltr)	50 (189)	51.5 (195)
Operating Weight - lbs (kg)	22830 (10355)	21266 (9646)

na = Not Applicable, np = Not Published

UNCONTROLLED COPY

This Case website contains records of competitive equipment. CNH assumes no responsibility or liability for reports, photography, availability, pricing, taxes or duties, or warranty information of the competitive equipment information contained or not contained regarding the competitive equipment. The User agrees to indemnify other personnel under its control against any and all liability, expenses, attorney fees, and damages arising from competitive equipment obtained from this website, including any claims alleging facts that if true would constitute a breach of the terms and conditions. For more information, view our full legal terms and conditions.

JOHN DEERE
650 K LGP

KOMATSU
D 39 PX-23

John Deere PowerTech PWS 4045	Komatsu SAA4D95LE-6
Tier 4	Interim Tier 4
104 (78)	105 (78)
not published	107 (79)
2200	2200
350 (475)	not published
276 (4.5)	199 (3.26)
Hydrostatic	Hydrostatic
5 (8)	5.3 (8.5)
5 (8)	5.3 (8.5)
33600 (147)	31473.2 (140)
No	No
No	No
28 (711)	25 (635)
40	39
1	1
7	6
7 ft 9 in (2349)	7 ft 9 in (2360)
Gear Type Pump	Variable Displacement Piston
21 (80)	26 (99)
PAT	PAT
2.6 (2)	3.14 (2.4)
9 ft 7 in (2921)	10 ft 8 in (3250)
13 ft 9 in (4179)	14 ft 5 in (4385)
9 ft 1 in (2758)	9 ft 4 in (2845)
61.9 (234)	50.2 (190)
20974 (9514)	21675 (9830)

any information, specifications, condition
ment. CNH is not responsible for the
CNH, its officers, agents, employees, and
out of or relating to the use of any record of
stitute a breach by the User of these terms

