



# MME20 MME25

## Electric Vertical Mast Lifts

- Up to 25 ft. (7.6 m) Platform Height Indoors and 31 ft. (9.6 m) Working Height Indoors
- Direct Electric Drive for Greater Duty Cycle and Smoother Controls
- AGM Maintenance-Free Batteries Standard
- Lifetime Roller Mast Construction for Maintenance-Free, Smooth Operation
- Lowest Ground Pressure with Wide Non-Marking Tires
- 350 lbs. (159 kg) Unrestricted Platform Capacity
- Glide-Out Deck Extension with Lift-Up Gate
- Rugged Steel Platform and Gate Construction
- Leak Containment System® Available - Patent #11,112,060



**Better Productivity, Accessibility and Durability**

**Standard Features**

**Work Area**

Roll-Out Deck Extension  
Lanyard Attachments (2)  
110v Power to Platform

**Performance**

Direct Electric Drive  
Fully Proportional Drive and Lift Controls  
Up To 25% Gradeability

**Power**

AGM Batteries  
Battery Charge Indicator  
Single 110v Receptacle at Chassis for Common Plug  
Connection for Battery Charger and Power to Platform

**Serviceability**

Lubrication-Free Bearings  
Easy Maintenance Access to Mechanical and Electrical Components  
Logically Grouped Components and Numbered Wiring for Easy Reference

**Safety**

Lift Control Orientation Designed to Mitigate Entrapment  
Dedicated Compartments Protect Electrical and Hydraulic Components  
Emergency Shut-Off at Platform and Lower Controls  
Non-Skid Metal Deck Construction  
Descent Alarm  
Drive Speed Interlock  
Multi-Axis Tilt Sensor  
Multiple Disc Brakes  
Automatic Parking Brake

**Other Features**

Removable Upper Controls  
Voltage-Compensating  
Fully-Automatic Battery Charger  
Hour Meter  
Machine Tie Downs  
Non-Marking Tires  
All Motion Alarm  
Fork Lift Pockets  
Flashing Beacon

**Optional Features**

Leak Containment System® (LCS) Patent #11,112,060  
Proactive Platform Safety System® (PPSS)  
900W Inverter  
Cold Weather Package  
Ceiling Grid Platform (22 in. x 22 in. / 56 cm x 56 cm)  
Tool Tray  
Second Year Extended Warranty



**MEC Aerial Work Platforms**

**Tel: 559.842.1500 | Fax: 559.842.1520**  
Toll free: 1.877.MEC LIFT | 1.877.632.5438  
1401 S. Madera Avenue, Kerman, CA 93630 | USA  
Email: info@MECawp.com | www.MECawp.com

MEC®, Leak Containment System® & Proactive Platform Safety System® are registered trademarks of California Manufacturing & Engineering Co., LLC. Leak Containment System® is Patent #11,112,060.

97032 DTD 1221

Models	MME20	MME25
<b>Heights</b>	<b>U.S./Metric</b>	<b>U.S./Metric</b>
Indoor Working Height*	26 ft.* / 8 m*	31 ft.* / 9.6 m*
Outdoor Working Height*	22 ft.* / 6.8 m*	26 ft.* / 8 m*
Indoor Platform Height	20 ft. / 6 m	25 ft. / 7.6 m
Outdoor Platform Height	16 ft. / 4.8m	20 ft. / 6 m
Guardrail Height	43.3 in. / 1.1m	
Stowed Height	78.35 in. / 1.99 m	
Ground Clearance	2.36 in. / 6 cm	
<b>Dimensions</b>		
Length - Overall	54.7 in./1.39 m	56.7 in./1.44 m
Chassis Width	30 in./0.76 m	31.5 in./0.80 m
Platform Length	29.5 in. / 0.75 m	
Roll-out Deck Length	21 in. / 53 cm	
Platform Width	28.5 in. / 0.72 m	
Total Lift Capacity	350 lbs. / 159 kg	
Personnel Capacity	1 person	
Roll-out Deck Capacity	350 lbs. / 159 kg	
<b>Speed</b>		
Raise/Lower Speed	23s / 25s	29s / 32s
Drive Speed (Stowed)	2.5 mph / 4.0 km/h	
Drive Speed (Elevated)	0.7 mph / 1.1 km/h	
<b>Performance</b>		
Gradeability	25%	
Turning Radius (Inside)	0 in. / 0 m	
Weight**	2,740 lbs.** / 1,243 kg**	3,310 lbs.** / 1,501 kg**
Power Source	2 x 12V 115Ah AGM Batteries	
Controls	Proportional	
Tires	12.7 in. x 3.9 in. / 323 mm x 100 mm	

\*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

\*\*Weight may vary with certain options or configurations.



**Important** - MEC mast lifts must be on a hard level surface while elevated.

**Warranty** - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

**Meets or exceeds** the requirements of ANSI A92.20 and CSA B354.6.

**Specifications** subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: