

ASSEMBLED DIMENSIONS (W X D X H)

75.75 X 31 X 76 IN. (192.4 X 78.7 X 193 CM)

PACKAGE DIMENSIONS (W X D X H)

76.75 X 31.75 X 7 IN. (195 X 80.7 X 17.8 CM)

WEIGHT

165 LB (74.8 KG)

LOAD CAPACITY

1,500 LB (680 KG). COMBINED WEIGHT OF USER + MATERIALS

WORKING HEIGHTSFROM 28 TO 71.5 IN. (71.1 TO 181.6 CM). 2 IN. (5 CM) INCREMENT
ADJUSTABLE HEIGHTS**REACH**12 FT (3.7 M). STACKABLE UP TO 2 UNITS HIGH FOR 18 FT (5.5 M)
REACH**FINISH**

POWDER COATED

PLATFORMPLATFORM WITH TRAP DOOR 9/32 IN. (15 MM) PLYWOOD, SLIP-
RESISTANT**STRUCTURE**

1.75 IN. (4.5 CM) SQUARE TUBE. 16 GAUGE STEEL

OPTIONSGUARDRAILS SYSTEM (I-BMSGR)
SET OF 4 OUTRIGGERS WITH CASTERS (I-BMSO4)**CASTERS**

6 IN. (15 CM) DOUBLE LOCKING HEAVY DUTY

COMPATIBLE WITH

BILJAX, BUFFALO, WERNER, UST AND METALTECH BAKER*

STANDARDS

ANSI, CSA AND OSHA

