



EMPOWERED BY INNOVATIVE ENGINEERING

1.866.323.0042



The Blaze 400 and 600 TURBO & TURBO II (LP/NG/OIL-FIRED)

RECIRCULATING CAPABILITIES



GROUND BREAKING FEATURES:

- 5,500/6,500 CFM Highest in its Class
- Ductability: 150 ft.
- Whisper Quiet Operation
- 220 °F Temperature Rise
- Recirculating Capabilities
- Full Load Amps: 8.5A (400) 11.5 (600) 17 (600 Turbo II)
- Forklift Pockets/Lifting Bar

The Blaze 400 & 600 TURBO and TURBO II High Performance Portable Heater



MORE FEATURES:

- Digital Panel Mounted Voltmeter
- Multiple Firing Rates
- Interchangeable Burners
- Stainless Steel Heat Exchanger
- Easy LP/NG Switchover
- Beckett Burner Options for both Oil and Gas
- Redundant Fail Safe Control System
- Oil Pressure Gauge
- Thermostat Operation
- Genysis Beckett Controller
- Optional 70 and 100 Gallon Fuel Tanks
- CSA/UL Approved
- 42 US Gallon Onboard Fuel Tank

DISTRIBUTED BY:



The Blaze 400 & 600 TURBO and TURBO II Introducing 120% full containment on 400 and 600 models



120% FULL SPILL CONTAINMENT. COMPLETE PROTECTION FOR TANK, BURNER LINES, FILTER AND PUMP. AVAILABLE WITH OUR 42 AND 70 US GALLON FUEL TANKS.



EASY ACCESS TO FILTER, FUEL FILLER AND BURNER AREA

