

Specifications – Campo Blaze 600 Diesel



EMPOWERED BY INNOVATIVE ENGINEERING
1.866.323.0042



The Blaze 400 and 600 TURBO (LP/NG/OIL-FIRED)

GROUND BREAKING FEATURES:

5,500 CFM Highest in its Class
Ductability: 150 ft.
Whisper Quiet Operation
220 °F Temperature Rise
Recirculating Capabilities
Full Load Amps: 8.5A (400) 11.5 (600)
Forklift Pockets/Lifting Bar

RECIRCULATING CAPABILITIES



The Blaze 400 & 600 TURBO High Performance Portable Heater

MORE FEATURES:

Digital Panel Mounted Voltmeter
Multiple Firing Rates
Interchangeable Burners
Stainless Steel Heat Exchanger
Easy LP/NG Switchover
Pressure Gauges on Inlet and Manifold
Riello & Beckett Burner Options for both Oil and Gas
Redundant Fail Safe Control System
Oil Pressure Gauge
Thermostat Operation
Genysis Beckett Controller
CSA/UL Approved
42 US Gallon Onboard Fuel Tank



Features:

- Input BTU/h: 588,000
- Indirect Oil Fired
- Beckett Burner
- 240 °F + Heat Rise
- Fuel Tank: 42 US Gallons (Optional 100 US Gallon tank available)
- Whisper Quiet Operation
- Air Volume: 5,500 CFM
- Up to 3" Static Pressure
- Recirculating Capabilities
- Thermostat Operation
- Genysis Primary Controller
- Digital Panel Mounted Voltmeter
- Redundant Fail Safe Control System
- Oil pressure gauge, Spin-off Filter
- Lifting Bar
- Forklift Pockets
- Weight: 500 lbs.
- Dimensions: 76.7" X 31" X 57.6"
- Full Load Amps: 11.5
- Power Supply: 120 Volt, 15A
- Air Outlets: Two 12" or 1 X 16"
- Air Inlets: Two 12" or 1 X 16"

CSA/UL Approved * Certified to CSA/UL standards by OMNI