

IDH200QR

Available in Oil/Diesel or LP/NG

A compact, efficient, durable and reliable indirect fired heater, with the ability to recirculate for fuel efficiency.



Features:

- Proven & reliable commercial grade burner
- Over 81% efficiency
- •Proven "Multi-Pass" Stainless Steel Heat Exchanger provides excellent efficiencies.
- •Fully independent fan & combustion air provides consistent and dependable operation in cold weather and ensures pre-heating to eliminate cold air delivery at start-up
- •High static pressure/high volume fan provides excellent CFM and static.
- •12" Outlet that can accommodate up to 100ft. of supply duct
- •12" Intake that can accommodate up to 50ft. of return duct to significantly reduce fuel consumption.
- Compact design with pneumatic wheels and handles to allow for easy transport
- Durable powder coat finish
- Optional remote thermostat available
- •Ball Valve Switchover from Propane to Natural Gas
- CSA Approved

Specifications:

Heating Capacity: 170,000 BTU/h
Fuel Requirement: Oil/Diesel or LP/NG

Heated Air Volume: 1,610 CFM Maximum Static Pressure: 5.0"

Discharge Temp. (Oil/Diesel): Up To 230°F (110°C) Fuel Tank Capacity (Oil/Diesel): 18 US Gallons Approx. Run Time (Oil/Diesel): 14-16 hrs

Total duct length (intake and supply), maximum 100 feet

Discharge Temperature (LP/NG): Up To 190°F (88°C) Supply Gas Pressure (LP/NG): 7-14"wc (1/2PSI) Manifold Pressure (LP/NG): 3.5"/NG - 1.8"/LP Overall Dimensions (LxWxH): 52" x 22" x 36"

Approximate Dry Weight: 209lbs
Approximate Weight w/ Fuel: 328lbs
Required Power: 120V/15amp/60Hz