

E3000 5100056440

Home >> Catalog >> Products >> Heating >> Hydronic Heaters >> Hydronic Surface Heaters >> **E3000**



E3000

Material number 5100056440

Equipped with a lift bail and 6 kW generator.

Product details

Highlights

- Powerful positive displacement pumps
- Dual hose reels

Comes with

•Includes operator's manual

Technical specifications

E3000

GENERATOR	Metric
Regulation [U] - Steady State	6,0 %
Generator Manufacturer	Mecc Alte
Output voltage	120 V
Nominal power	6 kW
Genset	yes
Output current 1~	30,0 A
Generator specification	Brushless with capacitor
Output frequency	60 Hz
Insulation class	Н
OPERATING FLUIDS	Metric
	840,0
Utilizable tank capacity Fuel Tank capacity	
	871,0
Oil volume	3,800 I
Run Time (100 %)	81,0 std
Fuel Consumption with genset	12,7 L/Std
Fuel Consumption no genset	10,4 L/Std
Fuel specification	Winter Blend Diesel No. 2
Run Time (75 %)	108,0 std
ENGINE	Metric
Cylinder	3
Cooling	Water-cooling
Engine Manufacturer	Kohler
Cylinder capacity	1.028 cm3
Operating Engine speed	1.800 1/min
Engine type	Diesel engine

Errors and omissions are reserved. The information in this data sheet is based on present knowledge. However, this neither guarantees specific product features nor establishes a legally valid contractual relationship.

SHIPPING AND STORAGE	Metric
Shipping weight (with Trailer)	4.076,0 kg
ELECTRICAL - OUTPUT DETAILS	Metric
Nominal current	20,00 A
	120 V
Nominal voltage	120 V
ELECTRICAL SYSTEM	Metric
Temperature monitor	digital
ENVIRONMENT DATA	Metric
Operating temperature range	38 - 82 °C
MECHANICAL DETAILS	Metric
Gross Axle Weight Rating	2.304 kg
Operating weight	4.076,0 kg
Length	4.600 mm
Lift Bail - quantity	1
Dry Weight	3.406,0 kg
Height	2.400 mm
Length hose	914 m
Gross vehicular weight	4.076,0 kg
Width	2.300 mm
THERMAL - OUTPUT DETAILS	Metric
Heater, Net output (Diesel)	94,00 kW
Throughput per loop	1.003 L/Std
Capacity Thaw max. (Std)	557 m2

Errors and omissions are reserved. The information in this data sheet is based on present knowledge. However, this neither guarantees specific product features nor establishes a legally valid contractual relationship.

Tires	22575R15 D	
CHASSIS	Metric	
Capacity Frost max. (w/acc)	2.508 m2	
Number of Hose Reels	2	
Capacity Thaw min. (Std)	279 m2	
Efficiency (Diesel)	83,0 %	
Capacity Thaw max. (w/acc)	557 m2	
Capacity in concrete curing(A)	1.672 m2	
Capacity Air Heat max. (w/acc	14.866 m3	
Heat transfer fluid (HTF)	435	
Hose pressure (normal operatio	7,5 bar	
Gross Heat Input (HHV)(Diesel)	113,00 kW	
Capacity in concrete curing	557 m2	
Quantity Circulation Loops, up	2	
Frost prevention (Standard)	836 m2	

521 kg

384 kg

Electric brake

Please Note

Brake

Tongue Weight, max.

Tongue Weight, min.

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2024 Wacker Neuson SE