



TPB-73



TPB-90



TRC-30

TRENCHER

SPECIFICATION

MODEL	CHUCK SIZE inch	STROKE inch (mm)	BORE inch (mm)	IMPACT RATE B.P.M.	WEIGHT lb (kg)	LENGTH inch (mm)	AIR CONSUMPTION CFM (m ³ /min)	AIR INLET inch	HOSE SIZE inch (mm)
TPB-30	7/8x3-1/4 or 1x4-1/4	3-3/8(85)	1-3/4(44.45)	1,550	33(15)	22-1/4(564)	49(1.4)	3/8 NPT	1/2(12.7)
TPB-40	1x4-1/4	5-3/4(146)	1-3/4(44)	1,100	40(18)	26(660)	50(1.3)	1/2 NPT	3/4(19)
TPB-60	1-1/8x6 or 1-1/4x6	4(100)	2-1/4(57.15)	1,400	66(30)	25-3/8(645)	70(2)	3/4 NPT	3/4(19)
TPB-73	1-1/8x6 or 1-1/4x6	5-5/16(144)	2-1/4(57.15)	1,200	70(31)	27-3/16(690)	63(1.8)	3/4 NPT	3/4(19)
TPB-90	1-1/8x6 or 1-1/4x6	6(152)	2-5/8(66.67)	1,250	92.4(42)	28-1/2(723)	77(2.2)	3/4 NPT	3/4(19)
TRC-30	7/8x3-1/4 or 1x4-1/4	3-11/32(85)	1-3/4(44.45)	1,550	36(16.3)	29(736)	49(1.4)	3/8 PT	1/2(12.7)

Dynamic pressure: 90 PSI (0.6MPa) for all products