HUSQVARNA POWER CUTTERS



K 4000 WET

Applications

 Perfect to use when operator needs to cut indoors. Either wet or dry applications.

Benefits

- Elgard[™], the advanced electronic overload protection system, varies the rotation speed to warn of an approaching overload.
- K 4000 Wet features pop-up carbon brushes, which increase motor life.
- · Lightweight, quiet-running, 2.4 hp.
- Convenient, high-efficiency water control for sufficient cooling and dust suppression.

	K 4000 Wet	
Item No.	967084001	
List price	\$1,219.00	



Blade, in (mm)	14 (350)
Cutting depth with vac unit, in (mm)	4-1/2 (119)
Dry cutting vacuum attachment (p/n 523095001)	
Cutting depth without vac unit, in (mm)	5 (127)
Electric motor, volts	120
Rated output, hp (watts)	2.4 (1,800)
Rated current, amps	15
Weight including cable, not including cutting equipment or vac unit lbs (kg)	17.4 (7.9)
Weight including cable and vac unit, not including cutting equipment, lbs (kg)	19.6 (8.9)
Elgard™, overload protection	Yes
"Pulling" rotation (downcutting)	Yes
Simple blade change	Yes
Replaceable arbor bushing	Yes
Sound power level Lwa, dB(A)	105
Sound pressure level, dB(A)	95
Vibration handle equivalent, m/s ²	3.5
Wet kit	Yes
Recommended minimum size generator. kW*	5
Wire / Cable / Extenison Cord size	12AWG / 50 feet
Wire / Cable / Extenison Cord size	10AWG /100 feet

NOTICE! Good motor performance depends on proper voltage. Extension cables that are too long and/or which have a gauge that is too small, reduce power to the motor under load, resulting in reduced output or malfunctions.



HUSQVARNA **POWER CUTTERS**



K 4000 CUT-N-BREAK

Applications

- · Perfect to use when operator needs to cut indoors. Designed for
- Make cuts up to 16" with the cut-n-break method.

Benefits

- Elgard[™], the advanced electronic overload protection system, varies the rotation speed to warn of an approaching overload.
- K 4000 Cut-n-Break features pop-up carbon brushes, which increase motor life.
- · Lightweight, quiet-runnning, 2.4 hp.
- · Convenient, high-efficiency water control for sufficient cooling and dust suppression.

	K 4000 Cut-n-Break	
Item No.	967083301	
List price	\$2,392.00	



Blade, in (mm)	9 (228)
Cutting depth, in (mm)	16 (400)
Electric motor, volts	120
Rated output, hp (watts)	2.4 (1,800)
Rated current, amps	15
Weight including cable, not including cutting equipment or Vac unit, lbs (kg)	18 (8.2)
Weight of Vac unit, lbs (kg)	n/a
Elgard™, overload protection	Yes
"Pulling" rotation (downcutting)	Yes
Simple blade change	Yes
Replaceable arbor bushing	NO
Sound power level Lwa, dB(A)	109
Sound pressure level, dB(A)	95
Vibration handle equivalent, m/s ²	3.4
Wet kit	Yes
Recommended minimum size generator. kW*	5
Wire / Cable / Extenison Cord size	12AWG / 50 feet
Wire / Cable / Extenison Cord size	10AWG /100 feet

NOTICE! Good motor performance depends on proper voltage. Extension cables that are too long and/or which have a gauge that is too small, reduce power to the motor under load, resulting in reduced output or malfunctions.

