



## Lightweight and easy to transport, and operate.

Leave your 2x4 behind and pick up your Uni-Screed!

- Specially designed to permit a single operator to quickly and easily level and consolodate an entire area.
- Multi-adjustable handle to meet operator needs and more efficient handling.
- Handle vibration is minimized with our impact absorbing mounting system to optimize control and operator comfort.
- Superior control is achieved with our responsive handle mounted throttle and on/off switch.
- High frequency vibration disperses and levels concrete without build-up.
- · Form and free screed.
- · Lightweight, easy to transport to and around job sites.
- Blade design permits cutting and smoothing in a single operation.
  Interchangeable blades with other leading wet screed units.
  Genuine Honda engine.

## **Options**

- Blades Available In:
  4' (1.2m), 6' (1.8m), 8' (2.4m), 10' (3.0m), 12' (3.7m), 14' (4.5m), 16' (4.9m)
- Magnesium coated.
- Blades are interchangeable with other popular brands.





	Specification Uni-Screed
Handle (fully adjustable)	28lbs (12.7kg)
Blades	
4' (1.2m)	6.41lbs (2.9kg)
6' (1.8m)	9.6lbs (4.4kg)
8' (2.4m)	12.8lbs (5.8kg)
10' (3.0m)	16.0lbs (7.3kg)
12' (3.7m)	19.2lbs (8.7kg)
14' (4.5m)	22.4lbs (10.2kg)
16' (4.9m)	25.6lbs (11.6kg)
Engine	1.3hp, 35cc, recoil start, air cooled, single overhead cam cylinder
Fuel Capacity	0.17 gal (0.65L)
Estimated Running Time	1.1hrs @ 7000rpm
Weight (dry)	27.9lbs +blade (12.7kg +blade)
Weight (operating)	29.6lbs +blade (13.5kg +blade)
Sound Power	50 Dba
Vibration	<9 m/s²

Additional information on accessories and consumables for our Uni-Screeds is available through our website, or contacting one of the Bartell Family numbers below.







