

TuffTruk MULTIQUIR

Zero Emissions. Endless Possibilities.



MULTIQUIR TUFFTYUK

EarthSmart[™]

The compact
TuffTruk is ideal
for interior demolition,
environmental remediation,
general construction,
landscaping and utility
work.





Available with a Polyethylene Tub



Integral battery charger uses standard 120 Volt power and features overcharge protection.

Zero emissions — easy charging!

- TuffTruk Model TB11E features a rechargeable, zero emission, high torque battery drive and provides solid eight hour run time under full load.
- Long-lasting charge lasts two to three days working under typical conditions.
- Rechargeable battery model has regenerative braking system to help slow down when stopping; this generates power back to the battery to increase efficiency and range.
- Quiet operation produces very low noise 69 dBa using rechargeable battery.

A compact workhorse

- **True 4-wheel drive** and wide flotation tires provide traction on muddy or rough terrain, with excellent climbing ability.
- **Excellent maneuverability** with 40° articulation angle and 58-inch turning radius.
- **Rugged steel tub** carries up to 10.6 ft³ of material or debris and passes through 36-inch wide openings. Optional 7 ft³ tub allows access through 32-inch openings.

Adapts to your requirements with multiple, easy-to-install accessories.



TuffTruk Extension Kit — **TTE** — 33.4 or 29.0 inch width, ideal for increased capacity when carrying light loads. (Steel tub only)



TuffTruk Dump Handle — **TTH** — for added convenience when discharging tub uphill.



TuffTruk Snow Plow — **TSP** — perfect for displacing snow during poor weather conditions.



TuffTruk Flatbed — **TFB33 and TFB29** — 33.4 or 29.0 inch width, ideal for transporting heavy bags of material.



TuffTruk 2-Inch Towing Hitch — **TBH** — offers various height positions for different size trailers.




Optional 7 ft³ clip-on tub — TT7 — allows access through narrow 32-inch passageways.



Specifications

Model	TB11E	TB11G	TB11PE	TB11PG
Tub Material	Steel	Steel	Polyethylene	Polyethylene
Tire type	Pneumatic	Pneumatic	Pneumatic	Pneumatic
Wheel base in.	29.5	29.5	29.5	29.5
Width in.	34.5	34.5	34.5	34.5
Length in.	68.5	68.5	68.5	68.5
Height in.	38	38	38	38
Weight lb.	561	396	561	396
Maximum payload capacity lb.	990	990	990	990
Capacity ft ³	10.6	10.6	10.6	10.6
Power Source	DC brushless motor 1300W / 24V	Honda GX200 5.5 HP Gas Engine	DC brushless motor 1300W / 24V	Honda GX200 5.5 HP Gas Engine
Battery type	2x12 volt AGM deep cell batteries	N/A	2x12 volt AGM deep cell batteries	N/A
Starting system	Electric	Manual recoil	Electric	Manual recoil
Drive and controls	4x4 - 24 volt motor gearbox	4x4 - Hydrostatic system	4x4 - 24 volt motor gearbox	4x4 - Hydrostatic system
Fuel capacity gal. (liter)	None	0.682 (3.1)	None	0.682 (3.1)
Travel speed forward - mph	0 to 3.5	0 to 4	0 to 3.5	0 to 4
Travel speed reverse - mph	0 to 1.5	0 to 1.5	0 to 1.5	0 to 1.5
Gradability	25%	25%	25%	25%
Oscillation	6°	6°	6°	6°
Articulation	40°	40°	40°	40°
Noise level dBa	69	96	69	96

Optional Clip-On Attachments					
Model	Description	Weight lb.	Dimensions LxWxH in.		
TBH	Towing Hitch — 2-inch diameter ball	19	28x16x8		
TSP	Snow Plow — includes front tool bar attachment bracket	66	45x19x21		
TBLADE	Snow Plow — replacement blade only	55	45x11x5		
FTB	Snow Plow — front tool bar attachment only	15	50x16x11		
TFB33	Flatbed — 33.4 inch width	65	33.5x30x6		
TFB29	Flatbed — 29.0 inch width	52	30x28.5x6		
TLP	Log Pole — 2 pieces	10	19x5x8		
TTE	Tub Extension Kit — for light material only* ^	20	34x28x6		
TTH	Tub Dump Handle — Steel Tub	4	19x5x5		
TTHP	Tub Dump Handle — Polyethylene Tub	4	19x5x5		
TT7	Steel Tub only, 7.0 ft ³ (660 lbs. capacity)	65	35x28x25		
TT11	Steel Tub only, 10.6 ft ³ (960 lbs. capacity)	80	35x33.5x23		



^{*} Increases capacity for lightweight material such as hay, mulch, and garden trimmings.

^ Steel tub only

