F501



- Honda GX160 OHV 4-stroke mini engine
- 91.4 cm (36") tilling width suitable for mid-sized gardens
- 2-forward speeds plus reverse for ease of use
- Ergonomically arranged controls for safe, convenient operation
- · Three-way adjustable handlebar
- Tilling and edging flowerbeds and vegetable gardens



SPECIFICATIONS			
TILLER TYPE	MID TINE	TILLING WIDTH	91.4 cm (36.0 in.)
ENGINE TYPE	4-STROKE; OHV	TINE DIAMETER	28.0 cm (11.0 in.)
Honda ENGINE MODEL	GX160T2	TINE SPEED @ MAX. TORQUE SPEED TRANSMISSION TYPE	80/113 RPM
DISPLACEMENT	163 cc (10.0 CID)		CHAIN DRIVE
FUEL CAPACITY	2.50 L (0.55 lmp. gal.)		
RECOMMENDED FUEL	REGULAR UNLEADED GASOLINE (87 OCTANE)	TRANSMISSION SPEED(S)	2-FORWARD / 1-REVERSE
STARTING SYSTEM	RECOIL STARTER	OVERALL LENGTH	132.0 cm (52.0 in.)
AIR CLEANER	DRY PAPER TYPE	OVERALL HEIGHT	99.5 cm (39.2 in.)
MUFFLER HEAT PROTECTOR	STANDARD	OVERALL WIDTH	95.5 cm (37.6 in.)
		DRY WEIGHT	61.0 kg (134.5 lb)
LUBRICATION SYSTEM	SPLASH	FURROW KIT	Available as an optional accessory on this
FOLDING HANDLE	N/A		model
3-POSITION HANDLE ADJUSTMENT	STANDARD	WHEEL WEIGHT KIT	N/A
4-POSITION HANDLE ADJUSTMENT	N/A	SIDE DISC KIT	STANDARD
TRANSPORT WHEELS	STANDARD	LAWN AERATOR KIT	N/A
ADJUSTABLE DEPTH BAR	STANDARD	WALKWAY BORDER/EDGER KIT	N/A
		LAWN DETHATCHER KIT	N/A
		DIGGING TINE KIT	N/A

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice.

See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

8/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.