

F220

- Honda GXV57 OHV 4-stroke mini engine
- 54.5cm (21.5") tilling width for moderate jobs
- Powerful, lightweight and emission compliant
- Quick and easy 3-way height adjustable handlebar folds and the front wheel retracts folds for transport or storage
- Tilling and edging flowerbeds and vegetable gardens



SPECIFICATIONS

TILLER TYPE	MID TINE	TILLING WIDTH	54.5 CM (21.5 IN)
ENGINE TYPE	4-STROKE; OHV; VERTICAL SHAFT; SINGLE CYLINDER	TINE DIAMETER	28.0 CM (11.0 IN)
Honda ENGINE MODEL	GXV57	TINE SPEED @ MAX. TORQUE SPEED	130 RPM
DISPLACEMENT	57 CC (3.5 CID)	TRANSMISSION TYPE	GEAR DRIVE
FUEL CAPACITY	0.70 LITRE (24.60 FL. IMP. OZ)	TRANSMISSION SPEED(S)	1-FORWARD
RECOMMENDED FUEL	REGULAR UNLEADED GASOLINE (87 OCTANE)	OVERALL LENGTH	120.0 CM (47.2 IN)
STARTING SYSTEM	RECOIL STARTER	OVERALL HEIGHT	97.5 CM (38.4 IN)
AIR CLEANER	DRY PAPER TYPE	OVERALL WIDTH	54.5 CM (21.5 IN)
MUFFLER HEAT PROTECTOR	STANDARD	DRY WEIGHT	22.5 KG (49.6 LB)
LUBRICATION SYSTEM	FORCED SPLASH	FURROW KIT	Available as an optional accessory on this model
FOLDING HANDLE	STANDARD	WHEEL WEIGHT KIT	N/A
3-POSITION HANDLE ADJUSTMENT	STANDARD	SIDE DISC KIT	Available as an optional accessory on this model
4-POSITION HANDLE ADJUSTMENT	N/A	LAWN AERATOR KIT	N/A
TRANSPORT WHEELS	STANDARD	WALKWAY BORDER/EDGER KIT	N/A
ADJUSTABLE DEPTH BAR	STANDARD	LAWN DETHATCHER KIT	N/A
		DIGGING TINE KIT	N/A

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice.

See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

©/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.