

DOSKO®

WWW.DOSKO.COM



WALK BEHIND
STUMP GRINDERS



MADE IN AMERICA



SEE THE DIFFERENCE A DOSKO MAKES

PORTABLE
WHEN NEEDED
HANDLEBAR FOLDS OVER UNIT



POWERED by
HONDA™

- A Portability**
Our 200-6HC "Mini" gives you extreme portability. The handlebars of the 200-6HC move forward and down. Combine this with its weight – just 134 lbs – and you can fit it in the back of an SUV or minivan with ease.
- B Operator Presence Handlebar**
The operator presence handlebar cuts all power to the stump grinder when you let go of the handle.
- C Throttle Control Lever**
The throttle control lever engages the cutter wheel.
- D Narrow Width**
With a width of just 23", the 200-6HC fits easily through even the narrowest of pathways and gates.
- E Side Discharge Frame**
Our unique side discharge frame moves cuttings out and away from the machine while grinding to keep your work area cleaner than with the use of channel frame stump grinders.
- F Heavy-Duty Belt**
Heavy-duty belt is easily accessible with the removal of two easy to reach bolts.
- G Cutter Teeth**
The 200-6HC "Mini" utilizes Leonardi™ M1® Blueshark™ teeth. The Leonardi tooth system is a no pocket system. Each tooth is rotatable in 120° increments for three fresh cutting edges with each tooth. Easily rotate or change teeth on the jobsite – no Allen wrench needed. "Mini" stump grinders come with standard black teeth, but red teeth for sand/clay soil and gold teeth for rocky soil are also available.



SEE THE DIFFERENCE A DOSKO MAKES



Our stump grinders produce a fine mulch that can be used for flower beds or around trees.

A



337-13HC

POWERED by
HONDA™

A

Portability

We've made it easy to transport our stump grinders wherever the job takes you. The 337, 357 & 620 Series are available with optional tow bar for transporting behind your vehicle. Our 691 Series self propelled model can be guided up a ramp for transport in a truck or trailer.

B

Operator Presence Bar

The operator presence handlebar cuts all power to the stump grinder when you let go of the handle.

C

Narrow Width

With widths between tires at 32" or less, our full-size stump grinders will fit easily through narrow pathways and gates.

D

Adjustable Handlebar

Handlebar angle adjusts with a simple locking pin system giving you optimum comfort and control.

E

Side Discharge Frame

Our unique side discharge frame removes cuttings out and away from the machine while grinding to keep your work area cleaner than with the use of channel frame stump grinders.

F

Heavy-Duty Belts & Bearings

Heavy-duty belt and idler bearings are easily accessible with the removal of two easy to reach bolts. Our belts require less tension resulting in reduced belt vibration and slipping. This also reduces excess load to the engine and cutter wheel bearings, increasing engine and bearing life.

G

Cutter Teeth

Need a new cutting edge on the jobsite? No problem. All our full-size stump grinders come standard Greenteeth.® These teeth can be rotated in three, 120° increments for a fresh cutting edge in minutes.





| Specifications | 200-6HC | | 337-13HC | | 357-13HE | | 620-20HE/ 620-25KE | | 691SP-20HE/ 691SP-25KE | |
|--|--------------------------|--------------------------|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|---|---|
| | STANDARD | METRIC | STANDARD | METRIC | STANDARD | METRIC | STANDARD | METRIC | STANDARD | METRIC |
| ENGINE | | | | | | | | | | |
| ENGINE | Honda GX200 | | Honda GX390 | | Honda GX390 | | Honda GX630/Kohler CH730 | | Honda GX630/Kohler CH730 | |
| DISPLACEMENT | 12.0 cu in | 196cc | 23.7 cu in | 389 cc | 23.7 cu in | 389 cc | 42.0/44.2 cu in | 688cc/725cc | 42.0/44.2 cu in | 688cc/725cc |
| FUEL | | | | | | | | | | |
| TYPE/TANK | Gasoline, 0.8 GAL | Gasoline, 3.0 L | Gasoline, 1.6 GAL | Gasoline, 6.0 L | Gasoline, 1.6 GAL | Gasoline, 6.0 L | Gasoline, 3.2 GAL | Gasoline, 12.1 L | Gasoline, 3.2 GAL | Gasoline, 12.1 L |
| STARTING | Recoil | Recoil | Recoil | Recoil | Recoil/ Electric* | Recoil/ Electric* | Electric* | Electric* | Electric* | Electric* |
| GENERAL | | | | | | | | | | |
| RPM OPERATING | 3600 RPM | 3600 RPM | 3600 RPM | 3600 RPM | 3600 RPM | 3600 RPM | 3600 RPM | 3600 RPM | 3600 RPM | 3600 RPM |
| OIL SENSOR | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| DIMENSIONS | | | | | | | | | | |
| LENGTH/(FOLDED) | 56" (36") | 142 (92 cm) | 58" | 147 cm | 58" | 147 cm | 58" | 147 cm | 85" | 218 cm |
| WIDTH | 23" | 58 cm | 32" | 81 cm | 32" | 81 cm | 32" | 81 cm | 30" | 76 cm |
| HEIGHT/(FOLDED) | 45" (23") | 114 (59 cm) | 51" | 130 cm | 51" | 130 cm | 51" | 130 cm | 56" | 142 cm |
| WEIGHT | 134 lbs | 61 kg | 300 lbs | 136 kg | 350 lbs | 169 kg | 400 lbs | 181 kg | 500 lbs | 227 kg |
| CUTTER WHEEL | | | | | | | | | | |
| DIAMETER | 10.5" | 27 cm | 14" | 36 cm | 14" | 36 cm | 14" | 36 cm | 14" | 36 cm |
| THICKNESS | 0.5" | 1.3 cm | 1-3/8" | 1 cm | 1-3/8" | 1 cm | 1-3/8" | 1 cm | 1-3/8" | 1 cm |
| BEARINGS (DIA.) (2) | 1" | 2.5 cm | 1-3/16" | 3 cm | 1-3/16" | 3 cm | 1-3/16" | 3 cm | 1-3/16" | 3 cm |
| TEETH TYPE | Leonardi™ Blueshark™ | Leonardi™ Blueshark™ | 500 Series Greenteeth® | 500 Series Greenteeth® | 500 Series Greenteeth® | 500 Series Greenteeth® | 700 Series Greenteeth® | 700 Series Greenteeth® | 700 Series Greenteeth® | 700 Series Greenteeth® |
| TEETH POCKETS | N/A | N/A | Reversible | Reversible | Reversible | Reversible | Reversible | Reversible | Reversible | Reversible |
| TEETH QUANTITY | 3 | 3 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 |
| TEETH DIMENSIONS (DIA. x THICKNESS) | 1" x 0.2" | 2.5 x .5 cm | 0.5" x 0.25" | 1.3 x 0.6 cm | 0.5" x 0.25" | 1.3 x 0.6 cm | 0.75" x 0.25" | 1.9 x 0.6 cm | 0.75" x 0.25" | 1.9 x 0.6 cm |
| CUTTER WHEEL RPM | 4700 RPM | 4700 RPM | 2200 RPM | 2200 RPM | 2200 RPM | 2200 RPM | 2500 RPM | 2500 RPM | 3000 RPM | 3000 RPM |
| DRIVE | Belt | Belt | Belt | Belt | Belt | Belt | Belt | Belt | Belt | Belt |
| | (1) AX37 | (1) AX37 | (1) Banded 3 Groove Power Band | (1) Banded 3 Groove Power Band | (1) Banded 3 Groove Power Band | (1) Banded 3 Groove Power Band | (1) Banded 4 Groove Power Band | (1) Banded 4 Groove Power Band | (1) 2 AX90 | (1) 2 AX90 |
| | 1600 Series Noram | 1600 Series Noram | Direct Drive | Direct Drive | Direct Drive | Direct Drive | Direct Drive | Direct Drive | Electromagnetic Clutch | Electromagnetic Clutch |
| CUTTING CAPACITY | | | | | | | | | | |
| ABOVE GRADE | 10" | 25 cm | 20" | 51 cm | 20" | 51 cm | 20" | 51 cm | 24" | 61 cm |
| BELOW GRADE | 9" | 23 cm | 16" | 41 cm | 16" | 41 cm | 16" | 41 cm | 18" | 46 cm |
| STUMP DIAMETER | No Limit | No Limit | No Limit | No Limit | No Limit | No Limit | No Limit | No Limit | No Limit | No Limit |
| GROUND TRAVEL | | | | | | | | | | |
| TRANSPORTATION | Push/Pull | Push/Pull | Push/Pull | Push/Pull | Push/Pull | Push/Pull | Push/Pull | Push/Pull | 0-3 MPH | 0-3 MPH |
| DRIVE | Wheel Hub | Wheel Hub | Wheel Hub | Wheel Hub | Wheel Hub | Wheel Hub | Wheel Hub | Wheel Hub | Hydrostatic | Hydrostatic |
| TIRES | 410-350 x 6" | 410-350 x 15.2 cm | 480 x 8" | 480 x 20.3 cm | 480 x 8" | 480 x 20.3 cm | 480 x 8" | 480 x 20.3 cm | 16-650 x 8" | 16-650 x 20.3 cm |
| BRAKE | Adjustable Brake Band | Adjustable Brake Band | Adjustable Brake Band | Adjustable Brake Band | Adjustable Brake Band | Adjustable Brake Band | Adjustable Brake Band | Adjustable Brake Band | Disc Brake w/ Adjustable Brake Pads | Disc Brake w/ Adjustable Brake Pads |
| TOW PACKAGE | N/A | N/A | Optional PN: 337-357TP | Optional PN: 337-357TP | Optional PN: 337-357TP | Optional PN: 337-357TP | Optional PN: 620-TP | Optional PN: 620-TP | N/A Self Propelled | N/A Self Propelled |
| MAXIMUM TOWING SPEED | N/A | N/A | 45 MPH | 72 KPH | 45 MPH | 72 KPH | 45 MPH | 72 KPH | N/A | N/A |

*Due to potential shipping restrictions and battery safety, units with electric start are not sold with batteries.

YouTube

See video online:
youtube.com/DoskoWeb

STUMPS WORST ENEMY



UNIQUE & PATENTED
SIDE DISCHARGE FRAME
MOVES CUTTINGS OUT AND AWAY FROM THE MACHINE

DOSKO®

OUR ROOTS

Dosko's roots trace back to southern California in 1983. When ownership changed in 2010, we moved our corporate office to Minnesota.

We offer a continued commitment to commercial quality, user-friendly design and portability. All Dosko equipment is engineered and manufactured to provide you years of reliable service.

Like what you see? Check out other Dosko product including brush chippers and log splitters.

20195 S. Diamond Lake Rd, Suite 100
Rogers, MN 55374

USA: 866.298.3659

International: +1.763.428.0302

SALES@DOSKO.COM | WWW.DOSKO.COM



Dosko® reserves the right to change engineering, specifications and options at any time without notice or obligation. Information contained within was current at time of printing and may change with new product development. Contact Dosko® for more information. Made in the USA. © 2015 Dosko® All rights reserved.