PROFESSIONALLY ENGINEERED TO INSPECT 3" TO 10" DIAMETER PIPELINES



PIPELINE PROBLEMS





PIPELINE INSPECTION SYSTEMS

CAM pro2

Features

- Rugged stainless steel housed 1.68" diameter self-leveling color camera
- 10.4" Daylight readable display
- 8" wheels for easy transport and maneuverability

Camera

- Rugged stainless steel housed 1.68" dia. self-leveling color camera with sapphire lens, 20 LED light ring and high resolution CCD element
- Flexible camera spring designed to navigate 3" P-traps
- Auto iris adjusts lighting automatically
- Impact-resistant polycarbonate light ring cover
- Industry standard 512HZ sonde



Reel & Frame

- Standard with 200 ft. of braided Fiberglass Premium 1/2" dia. push rod (reel capacity available up to 400 ft.)
- Secure-locking reel brake
- Rugged powder-coated steel tube and bar construction
- 8" wheels for easy transport and maneuverability

Monitor

- Audio/Video out jacks 10.4" Daylight readable display
- Record directly to USB flash drive
- Click touch controls and one touch recording
- 16 Pages of text writing with memory saves
- On screen footage counter
- Adjustable light controls
- Voice over recording (built-in) Rename files on flash drive after recorded
- 512 Hz sonde
- 2 Hour battery with built-in charger
- 8X Zoom function

(((WiFi Option Available)))

- One-Touch USB recording
- On-screen footage counter
- 8" wheels for easy transport and maneuverability







- WiFi enables users to record video with their mobile device
- Custom downloaded APP enables the user to see the video and take snap shots



WiFi Antenna



CAM ace

Features

- Rugged stainless steel housed 1.68" dia. color camera with sapphire lens
- 200 ft. of braided Fiberglass Premium 1/2" dia. push rod



Screen Cover



Standard Features and Specifications for All 3 Ecam ACE Pipeline Inspection Systems Include:



Camera

- Rugged stainless steel housed 1.68" dia. color camera with sapphire lens, 20 LED light ring and high resolution CCD element (optional self-leveling color camera available) • Flexible camera spring designed to navigate 3" P-traps
 • Auto iris adjusts lighting automatically • Industry standard 512HZ sonde • Impact-resistant polycarbonate light ring cover
- Camera options: .875" dia. color camera for inspecting 1½" 3" lines; 1.23" dia. color camera for inspecting 2" 4" lines.

- 5.4" LCD monitor with AR film for optimal viewing in sunlight encased in an anodized aluminum housing mounted to the reel
- Protective acrylic, anti-glare monitor shield Video output jack for recording option

Reel & Frame

• Rugged and portable powder-coated steel frame • Standard with 200 ft. of braided Fiberglass Premium 1/2" dia. push rod • Secure-locking reel brake • Heavy-duty screen cover closes to protect the monitor when in transit or storage, flips up as a sun shield and can be retrofitted to existing units.



For More Information, Call 800-833-1212 or Visit Our Web Site at www.electriceel.com



Note: Always refer to operator's manual and safety instructions before operating any pipeline inspection equipment.

ELECTRIC EEL MANUFACTURING CO., INC 501 W. Leffel Lane, Springfield, Ohio 45501-9985 937-323-4644 Toll-Free: 800-833-1212 FAX: 937-323-3767 E-mail: info@electriceel.com www.electriceel.com 4/16 LT-17