

Power Cutters Husqvarna K 970 Ring

The Husqvarna K 970 Ring is the world's first gas-powered cutter able to make 10.6" deep cuts with a 14" blade. This may seem impossible to anyone who uses standard power cutters, since 14" blades can normally only achieve a cutting depth of 5". However, we simply combined our unique and patented RingSaw technology, where the blade is driven from the periphery instead of its center, with the strong, easy to handle gas-powered cutter, the Husqvarna K 970. With the K 970 Ring, you can have the best of both worlds: the tried and tested ringsaw technology with its incredible cutting depth, and the ease of use and versatility of a gas-powered cutter.

- Cutting depth, max **270 mm**
- Blade diameter, max **370 mm**
- Output power **4.8 kW**

Daily exposure A(8)
m/s² **1,8**
Learn more about vibrations here

Article number : POWER CUTTER K 970 Ring 370 mm - 967 29 07-01

\$5,172.00

Get quote >

Our local salesman can give you **price quotes, book a demo or give you a call** to talk more.


Add to wish list >

Share

- Facebook
- Twitter
- Pinterest
- Email
- Print this page


FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



Deep cutting

Irregular deep cutting.



Sturdy and reliable

Less sensitive to outdoor conditions and fuel variations, thanks to the cylinder design and muffler with integrated heat deflector.

Long service intervals

A strong Poly-V belt combined with our maintenance-free DuraStarter™ and efficient filter-system Active Air Filtration™ ensure long service intervals.



Light and powerful

A light, compact and powerful machine with superior power-to-weight ratio.



Show more features ▾

SPARE PARTS | MANUALS



SPECIFICATIONS

Compare Power Cutters >

Engine

Output power	4.8 kW
Cylinder displacement	93.6 cm ³
Electrode gap	0.5 mm
Cylinders	1
Number of strokes	2-stroke engine

Cutting equipment

Cutting depth, max	270 mm
Blade diameter, max	370 mm
Blade thickness, max	5.6 mm
Peripheral speed, max	55 m/s

Dimensions

Product size length	784.6 mm
Product size width	224.2 mm
Product size height	430.7 mm
Weight	13.8 kg

Sound and noise

Sound power level, guaranteed (LWA)	115 dB(A)
Sound pressure level at operators ear	104 dB(A)

Vibrations

Vibrations left handle	2.7 m/s ²
Vibrations right handle	3.4 m/s ²

Certifications

CE certified	Yes
Cert CARB	CARB is not applicable for handheld above 65cc, see EPA.
Cert China	Yes
Cert EPA Phase 2	Yes
Cert EPA Phase 3	Yes
Cert EU Exhaust emission	Yes
Cert machine dir. 2006/42/EC Decl. No.	EURO TEST CERTIFICATE SEC/10/2286
Cert sound dir. 2000/14/EC Decl. No.	01/169/033

SPARE PARTS

Find your spare part article number

Here you can download the illustrated parts list for your power cutter.

[Download K 970 Ring parts list](#)

DIAMOND TOOLS

Series
Gold
Silver

R 1400 Diagrip

ELR

DI Ring Blade

FL



R 1400 Diagrip™

R 1420 Diagrip™

R 1445 Diagrip™

ELR 20 Ringsaw Blade

ELR 45 Ringsaw Blade

ELR 70 Ringsaw Blade

DI Ringsaw Blade

aterials

Reinforced concrete	-	●●	-	●●●	●●	-	-
Concrete hard	●●●	●●	●●	●●●	●●	-	-
Concrete medium	●●●	●●●	●●●	●●	●●●	-	-
Concrete soft	●●	●●	●●●	●	●●	●	-
Concrete	-	●●	-	-	-	-	-
Flint concrete hard	-	-	-	●●●	-	-	-
Granite	●●●	●●	●	●●●	-	-	-
Marble	●●●	●●	●	●●●	-	-	-
Natural stone	●●●	●●	●	-	-	-	-
Brick	●	●	●	-	●	●●●	-
Block	-	●	-	-	-	-	-
Abrasive	-	-	-	-	●	●●●	-
Green concrete (abrasive) soft	-	-	-	-	-	●	-
Ductile iron	-	-	-	-	-	-	●●●
Cured concrete hard	-	●●●	-	●●●	●●	-	-
Cured concrete medium	-	●●●	-	●●	●●●	-	-
Cured concrete soft	-	●●	-	●	●●	-	-
Trap-rock	-	-	-	●●●	-	-	-

●●● Optimal ●● Good ● Acceptable



Custom made tools

If you can't find a tool with the perfect fit we can custom make one for you, welcome to contact us.

Husqvarna K 970 Ring media gallery

ALL | PHOTOS | VIDEOS

Where to buy

Address, City or Zip code

Search



Find your location



You might need to accept that the browser uses your current location

More filters