




Husqvarna TS 60

A robust tile saw with a refined cart and rail system for perfectly straight cuts. The TS 60 is equipped with a patented water and slurry system for little to no mess. This includes an efficient recycling system that cleans water for reuse. Also, Elgard™ warns you of an approaching overload, and Electronic SoftStart™ allows starting with normal, slow acting fuses.



CLEAN WORK AREA

The Jet Stream Water Containment System keeps water and slurry in the cart trench, making it ideal for cutting indoors.



EASY TRANSPORT

The low weight, foldable legs and stable wheels facilitate transportation.



FLEXIBLE CUTTING METHOD

Switches between plunge cuts and mitre cuts with ease.



IDEAL FOR LONG CUTTING

The maximum cutting length of 700 mm and the large cutting table allows you to cut 50x50 cm tiles diagonally.

Features Husqvarna TS 60

- The large removable cutting table is easy to clean.
- Thanks to the refined recycling system which cleans water for reuse.
- Keeps water and slurry in the cart trench, making it ideal for cutting indoors.
- Enables bevel cuts between 22.5 and 45 degrees.
- The Elgard™ overload protection system allows you to always cut at maximum speed, for best performance.
- LED indication for machine overload provides increased productivity and motor life.
- Angle guide and adjustable stand are included to facilitate cutting.
- Provides starting with normal, slow acting fuses.
- Softstart™ lowers incoming current to reduce amperage when starting the motor.

TECHNICAL DATA	
Motor manufacturer	Husqvarna
Phases	1
Spindle diameter	15,9 mm
Blade diameter	250 mm
Max cutting depth	65 mm
Max cutting length	700 mm
Max tile size for diagonal cutting	508 mm
Water tank volume	12,4 lit
Weight (excl. cutting equipment)	36 kg
Product size, LxWxH	932x700x468 mm
Dimensions crated (LxWxH)	1016x558,8x711,2 mm
Weight incl. packaging	49,44 kg