



Bobcat MT52

Engine

Emissions Tier (EPA)	Tier 4
Engine Model	D722-E3B-8C-6
Engine Make	Kubota
Engine Cooling	Liquid
Engine Fuel	Diesel
Displacement	44 in ³
Number of Cylinders	3
Torque RPM	2,600 rpm
Maximum Governed RPM	3,600 rpm
Horsepower	20 hp

Performance

Rated Operating Capacity (SAE)	520 lb
Tipping Load	1600 lb
Operating Weight	2580 lb
Ground Pressure (Rubber)	4.7 psi
Travel Speed	3.5 mph
Travel Speed - Reverse	1.5 mph

Capacities

Fuel Tank	7 gal
-----------	-------

Hydraulic System

Pump Capacity	12 gal/ min
System Relief @ Quick Couplers	2,900 psi
Number of Tilt Cylinders	1
Auxiliary Std Flow	n/ a

General

Contract Codes	Mini- Track Loader
First Year of Production	2008

Controls

Vehicle Steering	Other
Lift and Tilt	Controlled by one hand lever

Dimension

Length	93.1 in
Width	35.6 in
Height	49.1 in
Height to Bucket Hinge Pin	71.2 in
Length of track on ground	34 in
Length without Attachment	72.4 in
Length with Standard Bucket	93.1 in
Width (with bucket)	3 ft
Reach @ Maximum Height	18.2 in
Dump Angle @ Maximum Height	50°
Ground Clearance	4.5 in
Angle of Departure	23°
Turning Radius	54.2 in

Features

Lift-Arm Support	☒
Auxiliary Hydraulics	☒
Spark Arrestor Muffler	☒
Bob-Tach Attachment System *	☒



Reverse Travel Stop Panel	■
Wide Track	□
Neutral Start Interlocks	■
Lift Arm Lockout With Manual Bypass	■
Tilt Lockout	■
Built-In Tie Down & Crane/ Lift Locations	■
Ride-on Platform	×

Some specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.