

 SHARE

Mini Track Loaders / MT55 Mini Track Loader Specifications & Options

Standard Optional Not Applicable

Units US

Bobcat MT55

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Displacement	55 in ³
Number of Cylinders	3
Horsepower	24.8 hp

Performance

Rated Operating Capacity (SAE)	550 lb
Tipping Load	1610 lb
Operating Weight	2610 lb
Ground Pressure (Rubber)	4.9 psi
Travel Speed	3.5 mph
Travel Speed - Reverse	1.4 mph

Capacities

Fuel Tank	7 gal
-----------	-------

Hydraulic System

Pump Capacity	12 gal/min
System Relief @ Quick Couplers	2,900 psi
Auxiliary Std Flow	n/a

Dimension

Length	93.1 in
Width	35.6 in
Height	49.1 in
Height to Bucket Hinge Pin	71.2 in
Length of track on ground	34 in
Reach @ Maximum Height	18.2 in

Features

Lift-Arm Support

Auxiliary Hydraulics

Spark Arrestor Muffler

Bob-Tach Attachment System

Reverse Travel Stop Panel

Wide Track

Neutral Start Interlocks

Lift Arm Lockout With Manual Bypass

Tilt Lockout

Built-In Tie Down & Crane/Lift Locations

Ride-on Platform

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.