

SSV

KUBOTA SKID STEER LOADER SSV65/SSV75

Excellent power and exceptional operator comfort bring new levels of performance and productivity to Kubota's SSV-Series Skid Steer Loaders.



SPECIFICATIONS

| Model | | SSV65 | SSV75 |
|---|---|-------------------------------------|---------------------------|
| Type of operator station | | Open CAB / Closed CAB | Open CAB / Closed CAB |
| Engine | | | |
| | Model | V2607-CR-TE4 | V3307-CR-TE4 |
| | Emission certification | Tier 4 | Tier 4 |
| | Gross HP (SAE J1995) | HP (kW)/rpm 64.0 (47.7)/2700 | 74.3 (55.4)/2600 |
| | Net HP (SAE J1349) | HP (kW)/rpm 61.3 (45.7)/2700 | 71.6 (53.4)/2600 |
| | Displacement | cu.in. (cc) 159.7 (2615) | 203.3 (3331) |
| | Cylinders | 4 | 4 |
| | Bore Stroke | in.(mm) 3.5 (87) × 4.4 (110) | 3.8 (94) × 4.8 (120) |
| | Aspiration | Turbocharged | Turbocharged |
| Loader performance | | | |
| | Rated operating capacity-50% tipping load | lbs. (kg) 1950 (885) | 2690 (1220) |
| | Tipping load | lbs. (kg) 3900 (1770) | 5380 (2440) |
| | Breakout force | Bucket | 5884 (2669) |
| | | Lift arm | 4850 (2200) |
| | Lift arm path | Vertical | Vertical |
| Power train | | | |
| | Standard tire size | 10-16.5-8PR | 12-16.5-10PR |
| | Chain size ASA# | 80 | 100 |
| | Travel speed | Low | 6.9 (11.1) |
| | | High | 11.1 (17.8) |
| | Traction force | lb. (kgf) 7339 (3329) | 8494 (3853) |
| | Ground clearance | in. (mm) 7.6 (193) | 8.1 (207) |
| Hydraulic system | | | |
| | Loader hydraulic flow | gpm (ℓ/min.) 18.0 (68.0) | 20.9 (79.0) |
| | Loader hydraulic pressure | psi (kgf/cm²) 3271 (230) | 3271 (230) |
| | Aux. hydraulic flow | Standard | 20.9 (79.0) |
| | | High | 30.4 (115.0) |
| Service refill capacities | | | |
| | Hydraulic tank | gal. (ℓ) 4.2 (16.0) | 4.2 (16.0) |
| | Fuel tank | gal. (ℓ) 25.4 (96.0) | 26.9 (102.0) |
| Operating weight (Include operator weight 165 lbs.) | | lbs. (kg) 7099 (3220) / 7319 (3320) | 8245 (3740) / 8466 (3840) |

EQUIPMENT

STANDARD EQUIPMENT

- Open CAB (ROPS/FOPS Level1)
- Top/Rear window
- Type of Control (Hand & Foot control/ISO pilot control)
- Suspension Seat
- 2" Retractable seat belt
- Fold down arm rests
- Dial throttle
- 12V electric outlet
- Radio Ready (Closed Cab only)
- Horn
- Backup alarm
- Work lights (Front 2/Rear 2)
- Side lights
- Bucket Cylinder Guards
- Protection for AUX coupler
- Mechanical quick coupler
- Heavy Duty Tire
SSV65 10-16.5
SSV75 12-16.5

OPTIONAL EQUIPMENT

- High flow hydraulics
- Multifunction lever
- 14 pin coupler for attachments
- Kubota Shockless Ride (KSR)
- Self leveling (on/off)
- Air ride suspension seat
- 3" Retractable seat belt
- Door lock key
- Various buckets and other attachments
- Tire options
- Hydraulic quick coupler
- Hazard Lamp/Turn Signals
- Strobe light
- Beacon light
- Polycarbonate door
- Additional counterweight
- Engine block heater
- ...and much more.

DIMENSIONS

SSV65 / SSV75

