

Engine

Emissions Tier (EPA)	Interim Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	66 hp
Turbocharged Engine	X
Engine Model	V2607-DI-TE3B-BC-I
Engine Make	Kubota
Displacement	159 in ³
Torque RPM	1,425 rpm
Number of Cylinders	4
Maximum Governed RPM	2,700 rpm

Performance

Rated Operating Capacity (SAE)	1,900 lb
Operating Capacity (50% of Tip)	3642 lb
Rated Operating Capacity (35% Of Tip)	1900 lb
Tipping Load	7283 lb
Operating Weight	7775 lb
Travel Speed	7.3 mph
Ground Pressure (Rubber)	5.03 psi
Travel Speed - Low	7.1 mph

Capacities

Fuel Tank	28 gal
-----------	--------

Hydraulic System

System Relief @ Quick Couplers	3,250 psi
Auxiliary Std Flow	16.9 gal/ min
Auxiliary High Flow	26.4 gal/ min
Number of Tilt Cylinders	2

General

Contract Codes	Compact Track Loader
First Year of Production	2008

Controls

Hydraulic (Lift and Tilt)	Dual Pedals
Control Option	SJC, ACS
Auxiliary Hydraulics Type	Fingertip

Dimension

Length	101.9 in
Length without Attachment	101.9 in
Length with Standard Bucket	130.3 in
Width	66 in
Width (with bucket)	68 in
Height	76.3 in
Height with Operator Cab	76.3 in
Height to Bucket Hinge Pin	118.2 in
Reach @ Maximum Height	30.9 in
Turning Radius	78.8 in
Length of track on ground	55.2 in
Track Width	12.6 in
Track Width - Optional	15.8 in
Ground Clearance	8.1 in
Standard Tracks	12.6 in



Dump Angle @ Maximum Height

42°

Features

Joystick Control	X
Air Conditioning	X
Backup Alarm	■
BICS System (Interlock)	■
Cab Heater	X
Operating Lights	■
Suspension Seat	■
Two Speed Travel	□
Deluxe Instrumentation	X
Engine Shutdown	■
Hydraulic Bucket Positioning	X
High Flow Option	X
Auxiliary Hydraulics	■
Bob- Tach Attachment System *	■
Power Bob- Tach *	X
ACS (Switchable Controls)	X
Ride Control	X
Horn	■

Data & specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.