



Bobcat T590

Configuration	Standard	Roller Suspension Option
Engine		
Emissions Tier (EPA)	Tier 4	n/a
Engine Cooling	Liquid	
Engine Fuel	Diesel	
Horsepower	66 hp	
Turbocharged Engine	X	
Engine Model	2.4L Bobcat Engine	n/a
Engine Make	Bobcat	n/a
Displacement	146 in ³	
Torque RPM	1,800 rpm	
Number of Cylinders	4	
Performance		
Rated Operating Capacity (SAE)	2,100 lb	1,950 lb
Operating Capacity (50% of Tip)	3000 lb	2786 lb
Rated Operating Capacity (35% Of Tip)	2100 lb	1950 lb
Tipping Load	6000 lb	5571 lb
Operating Weight	7822 lb	8007 lb
Travel Speed	7.1 mph	n/a
Travel Speed (2- speed option)	10.4 mph	n/a
Ground Pressure (Rubber)	5.2 psf	5.1 psi
Capacities		
Fuel Tank	36.5 gal	n/a
Hydraulic System		
System Relief @ Quick Couplers	3,500 psi	
Auxiliary Std Flow	17.1 gal/ min	
Auxiliary High Flow	26.7 gal/ min	
General		
Contract Codes	Compact Track Loader	
Controls		
Hydraulic (Lift and Tilt)	Dual Pedals	
Control Option	ACS, SJC	
Auxiliary Hydraulics Type	Finger Tip Control	
Dimension		
Length	133 in	
Length without Attachment	104.6 in	
Length with Standard Bucket	133 in	
Width	67 in	70 in
Width (with bucket)	68 in	74 in
Height	77.8 in	
Height with Operator Cab	77.8 in	
Height to Bucket Hinge Pin	119 in	
Reach @ Maximum Height	34.9 in	
Turning Radius	80 in	n/a
Length of track on ground	54.1 in	
Track Width	12.6 in	
Track Width - Optional	15.8 in	
Ground Clearance	7.4 in	n/a
Standard Tracks	12.6 in	
Dump Angle @ Maximum Height	42°	



Features

Joystick Control	X
Air Conditioning	X
Backup Alarm	■
BICS System (Interlock)	■
Cab Heater	X
Operating Lights	■
Suspension Seat	■
Two Speed Travel	□
Deluxe Instrumentation	X
Engine Shutdown	■
Hydraulic Bucket Positioning	X
High Flow Option	X
Auxiliary Hydraulics	■
Bob-Tach Attachment System *	■
Power Bob-Tach *	X
ACS (Switchable Controls)	X
Ride Control	X
Horn	■

Options & specifications are based on engineering calculations and are not actual measurements. Specifications are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions and other factors.