



Bobcat T300

Engine

Emissions Tier (EPA)	Tier 3
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	81 hp
Turbocharged Engine	X
Engine Model	V3800-DI-TE3
Engine Make	Kubota
Displacement	230 in ³
Torque RPM	1,600 rpm
Number of Cylinders	4
Maximum Governed RPM	2,400 rpm

Performance

Rated Operating Capacity (SAE)	3,000 lb
Operating Capacity (50% of Tip)	4604 lb
Rated Operating Capacity (35% Of Tip)	3000 lb
Tipping Load	9208 lb
Operating Weight	9702 lb
Travel Speed	6.6 mph
Ground Pressure (Rubber)	3.9 psi
Travel Speed - Low	6.6 mph

Capacities

Fuel Tank	26 gal
-----------	--------

Hydraulic System

System Relief @ Quick Couplers	3,300 psi
Auxiliary Std Flow	21.2 gal/ min
Auxiliary High Flow	37 gal/ min
Number of Tilt Cylinders	2

General

Contract Codes	Compact Track Loader
First Year of Production	2008

Controls

Hydraulic (Lift and Tilt)	Dual Pedals
Control Option	ACS, SJC
Auxiliary Hydraulics Type	Fingertip

Dimension

Length	114.5 in
Length without Attachment	114.5 in
Length with Standard Bucket	142.9 in
Width	78 in
Width (with bucket)	80 in
Height	80.9 in
Height with Operator Cab	80.9 in
Height to Bucket Hinge Pin	128.4 in
Reach @ Maximum Height	36.5 in
Turning Radius	34.2 in
Length of track on ground	63.7 in
Track Width	17.7 in
Track Width - Optional	12.6 in
Ground Clearance	8.7 in
Standard Tracks	18 in



Dump Angle @ Maximum Height

42°

Features

Joystick Control	X
Air Conditioning	X
Backup Alarm	■
BICS System (Interlock)	■
Cab Heater	X
Operating Lights	■
Suspension Seat	X
Two Speed Travel	□
Deluxe Instrumentation	X
Engine Shutdown	■
Hydraulic Bucket Positioning	X
High Flow Option	X
Auxiliary Hydraulics	■
Bob- Tach Attachment System *	■
Power Bob- Tach *	X
ACS (Switchable Controls)	X
Ride Control	X
Horn	■

Certain specification(s) are based on engineering estimates and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.