



# Bobcat MT85

## Engine

Emissions Tier (EPA)	Tier 4
Engine Model	D902- E3B- BC-1
Engine Make	Kubota
Engine Cooling	Liquid
Engine Fuel	Diesel
Displacement	55 in <sup>3</sup>
Number of Cylinders	3
Torque RPM	2,600 rpm
Maximum Governed RPM	3,600 rpm
Horsepower	25 hp

## Performance

Rated Operating Capacity (SAE)	850 lb
Tipping Load	2458 lb
Operating Weight	3110 lb
Ground Pressure (Rubber)	4.9 psi
Travel Speed	4 mph
Travel Speed - Reverse	2.4 mph

## Capacities

Fuel Tank	7 gal
-----------	-------

## Hydraulic System

Pump Capacity	12 gal/ min
System Relief @ Quick Couplers	2,900 psi
Number of Tilt Cylinders	1
Auxiliary Std Flow	n/ a

## General

Contract Codes	Mini- Track Loader
First Year of Production	2015

## Controls

Vehicle Steering	Other
Lift and Tilt	Controlled by joystick
Auxiliary Hydraulics Type	Controlled by fore and aft movement of hand lever

## Dimension

Length	106.2 in
Width	35.6 in
Height	54.6 in
Height to Bucket Hinge Pin	80.9 in
Length of track on ground	40.6 in
Length without Attachment	84.5 in
Length with Standard Bucket	106.2 in
Width (with bucket)	3 ft
Reach @ Maximum Height	18.6 in
Dump Angle @ Maximum Height	45°
Ground Clearance	8 in
Angle of Departure	24.1°
Turning Radius	58.3 in

## Features

Lift- Arm Support	☒
Auxiliary Hydraulics	☒
Spark Arrestor Muffler	☒



- Bob-Tach Attachment System\*
- Reverse Travel Stop Panel
- Wide Track
- Neutral Start Interlocks
- Lift Arm Lockout With Manual Bypass
- Tilt Lockout
- Built-in Tie Down & Crane/Lift Locations
- Ride-on Platform

\*Certain specifications are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.