



# Model 5700XP Specifications

**BATTERY-POWERED WALK-BEHIND SCRUBBER**  
Standard with FaST™ Foam Scrubbing Technology

Feature			
<b>Scrubbing System</b>			
Cleaning path (3 paths available)	28-inch/700 mm	32-inch/800 mm	36-inch/900 mm
Solution tank capacity	30 gallon/114 liter		
Scrub head types	Disk and cylindrical		
Scrub motors	(2) 0.6 hp/0.45 kW	(2) 0.6 hp/0.45 kW	(2) 1.0 hp/0.75 kW
Disk	(2) 0.75 hp/0.56 kW		
Cylindrical			
Brush speed	320 rpm/300 rpm/750 rpm		
Disk/HD disk/cylindrical			
Brush down pressure			
Disk	0-200 lb/0-91 kg		
HD Disk (800 mm only)	0-300 lb/0-136 kg		
Cylindrical	0-90 lb/0-41 kg		
Brush/pad driver quantity & dimensions			
Disk (D)	(2) 14-inch/355 mm	(2) 16-inch/405 mm	(2) 18-inch/455 mm
Cylindrical (L x D)	(2) 28 x 6-inch/ 700 x 150 mm	(2) 32 x 6-inch/ 800 x 150 mm	(2) 36-inch/ 900 x 150 mm
<b>Recovery System</b>			
Recovery tank capacity	40 gallon/151 liter (Includes demisting chamber)		
Vacuum fan			
Motor	0.8 hp/0.6 KW		
Stages	2-stage		
Water lift	73-inch/1,855 mm		
<b>Propelling System</b>			
Propel speed (variable to)	3.1 mph/5.0 km/h		
Batteries (36V system, charger included)			
Standard	(6) 6V, 235 AH		
Optional	(6) 6V, 335 AH		
Gradeability (Ramp climb)			
Full / Empty	6.0° / 8.0°		
<b>Machine Dimensions / Sound level</b>			
<b>Length</b>			
Disk	64-inch/1,625 mm		
Cylindrical	63-inch/1,600 mm		
<b>Width</b>			
Body	28.25-in/ 720 mm		
Scrub head			
Disk	30-inch/760 mm	34-inch/865 mm	38-inch/965mm
Cylindrical	30.5-inch/775 mm	34.25-inch/870 mm	38.25-inch/970 mm
Squeegee	37.5-inch/950 mm	42-inch/1,070 mm	45.5-inch/1,160 mm
Height	43-inch/1090 mm		
<b>Net weight</b>			
Less batteries	415 lb/188 kg		
With batteries (6) 235 AH 6-V	817 lb/371 kg		
With batteries (6) 335 AH 6-V	1,021 lb/464 kg		
Minimum aisle turn:	66.25-inch/1,680mm	67-inch/1,700 mm	67.5-inch/1725mm
Sound level (operator's ear)	75 dBa		
<b>Warranty</b>	Please refer to your local Tennant representative for information.		