

BID SPECIFICATIONS

BOBCAT 72" LANDSCAPE RAKE (MODEL 6B)

REQUIRED FEATURES

- Attachment must pick up rocks down to 3/4 in. (19 mm) in size.
- Attachment must break up clumps and clods.
- Side skis must be adjustable to provide depth control.
- Attachment will prepare ground for seed or sod and will aerate soil.
- Minimum working width will be 72".

SPECIFICATIONS

Weight	1130 lbs. (513 kg)
Working Width.....	72" (1829 mm)
Overall Width.....	78.6" (1998 mm)
Number of Tooth Bars.....	12
Number of Teeth (total).....	102
Capacity	14.3 ft ³ (0.40 m ³)

MOUNTING

- The landscape rake will be easily attached by means of hydraulic couplers and Bob-Tach™ mounting frame.
- Landscape rake will not hinder the standard lift arm actions of the loader.
- The hydraulic supply lines for the landscape rake will be routed through a hose guide location on the loader lift arm.

ATTACHMENT CONTROL

- Activation/deactivation of the landscape rake, and opening/closing the top cover of the landscape rake must be fingertip controlled from the operator seat without requiring operator to remove his/her hands from the loader steering levers.

SAFETY

- Entry and exit steps must be provided.
- Operation and safety decals must be displayed on the attachment.