

BID SPECIFICATIONS

BOBCAT LT112 TRENCHER

REQUIRED FEATURES

- Trenching widths must range from 4" to 8".
- Frame width must be no greater than 36".
- Maximum dig depth must be at least 24".
- Trencher must have the ability to attain 36" dig depth with optional equipment.
- Auger must be at least 12" in diameter and must be removable.
- A grease cylinder must be used for chain adjustment.
- Multiple chain options must be available.
- Carbide tooth kit must be available.
- Trench cleaner must be available.

SPECIFICATIONS

Operating Weight (without teeth)	615 lbs. (279 kg)
Overall Length	60.7" (1541 mm)
Standard Boom Length	39.4" (1000 mm)
Frame Width	36" (915 mm)
Auger Diameter.....	12" (305 mm)
Dig Depth.....	24"-36" (610 mm to 915 mm)
Flow Range	9 to 15 gpm (34 to 57 liters/min)
Maximum Operating Pressure	3000 psi
Trenching Widths Available.....	4" to 8"

MOUNTING

- The trencher will be easily attached by means of hydraulic couplers and Bob-Tach™ mounting frame.
- Trencher will not hinder the standard lift arm actions of the loader.

ATTACHMENT CONTROL

- Activation/deactivation of the trencher will be controlled from the operator seat or the operator standing area using fingertip controls without requiring operator to remove his/her hand(s) from the loader control lever(s).

SAFETY

- Entry and exit steps must be provided.
- Operation and safety decals must be displayed on the trencher attachment.