

BID SPECIFICATIONS

BOBCAT LT313 TRENCHER (4' DIG DEPTH)

REQUIRED FEATURES

- Trenching widths must range from 6" to 12".
- Frame width must be no greater than 60".
- Maximum dig depth must be at least 48".
- Trencher must have manual side-shift, 23" minimum, with availability of option to add hydraulic side-shift.
- Auger must have a minimum diameter of 12" and must be removable.
- A grease cylinder must be used for chain adjustment.
- Multiple chain options must be available.
- Carbide tooth kit must be available.
- Trench cleaner must be standard equipment.

SPECIFICATIONS

Operating Weight (without teeth)	980 lbs. (445 kg)
Overall Length	89.3" (2273 mm)
Standard Boom Length	65.5" (1664 mm)
Frame Width	56" (1422 mm)
Side-shift (manual).....	23.1" (587 mm)
Auger Diameter.....	12" (305 mm)
Dig Depth.....	48" (1219 mm)
Flow Range	15 to 22 gpm (57 to 83 liters/min)
Maximum Operating Pressure	3300 psi
Trenching Widths Available.....	6" to 12"

MOUNTING

- The trencher will be easily attached by means of hydraulic couplers and Bob-Tach™ mounting frame.
- Trencher will not hinder the standard lift arm actions of the loader.

ATTACHMENT CONTROL

- Activation/deactivation of the trencher will be controlled from the operator seat using fingertip controls without requiring operator to remove his/her hands from the loader steering levers.

SAFETY

- Entry and exit steps must be provided.
- Operation and safety decals must be displayed on the trencher attachment.