

BID SPECIFICATIONS BOBCAT AUGER, MODEL 10

REQUIRED FEATURES

- Auger must have a direct drive hydraulic motor.
- Must be able to accommodate up to 36" diameter bits.
- Will be able to dig at least 58" deep without the need for bit extensions.
- Various extensions must be available to give up to an additional 48" dig depth.
- Output shaft must be round.
- Mounting frames must be available to mount to excavators, loaders, mini loaders and loader backhoes.
- Auger must be able to drill a vertical hole even if the attachment carrier is not on level ground.

SPECIFICATIONS

Operating Weight (without bit).....	264 lbs. (120 kg)
Digging Depth (without extension)	58" (1473 mm)
Hydraulic Flow	6 – 17 gpm (23 – 64 liters/min)
Extensions Available	14", 24" and 48" adjustable

MOUNTING

- The auger will be easily attached by means of hydraulic couplers and Bob-Tach™ mounting frame.
- Auger will not hinder the standard lift arm actions of the loader.

ATTACHMENT CONTROL

- Activation/deactivation of the auger bit must be fingertip controlled from the operator seat or operator standing area without requiring operator to remove his/her hand(s) from the loader steering levers or mini loader, loader backhoe or excavator operating lever(s).

SAFETY

- Entry and exit steps must be provided on loader mounting frame.
- Operation and safety decals must be displayed on the auger attachment.