

# BID SPECIFICATIONS BOBCAT AUGER, MODEL 15C

## REQUIRED FEATURES

- Auger must have a direct drive hydraulic motor.
- Will be able to dig at least 62" deep without the need for bit extensions.
- Various extensions, for both round bits and hex bits, must be available to give up to an additional 48" dig depth.
- Must be able to accommodate up to 42" diameter bits.
- Auger output shaft will accommodate round or hex bits without the need for an adapter.
- Mounting frames must be available to mount to excavators, loaders, loader backhoes and work machine.
- Auger must be able to drill a vertical hole even if the attachment carrier is not on level ground.

## SPECIFICATIONS

Operating Weight (without bit).....	406 lbs. (184 kg)
Digging Depth (without extension) .....	62" (1575 mm)
Hydraulic Flow .....	8 – 22 gpm (30 – 83 liters/min)
Extensions Available .....	14", 24" adjustable, and 48" adjustable

## MOUNTING

- The auger will be easily attached by means of hydraulic couplers and Bob-Tach™ mounting frame.
- Auger will not hinder the standard lift arm actions of the loader or work machine.

## ATTACHMENT CONTROL

- Activation/deactivation of the auger bit must be fingertip controlled from the operator seat without requiring operator to remove his/her hand(s) from the loader steering levers or excavator or loader backhoe operating levers or work machine steering wheel.

## SAFETY

- Entry and exit steps must be provided on carrier mounting frame.
- Operation and safety decals must be displayed on the auger attachment.