SBU 160



Features & benefits

- AutoStart
- Energy recovery
- Solid Body concept
- Noise reduction
- Dust protection
- Overload protection valve
- Double tool retainer bars
- Integrated maintenance free accumulator

Applications

- Road construction
- Smaller trenching and demolition jobs
- Building renovation
- Landscaping
- Boulder size reduction in quarries

SBU Hydraulic Breakers for Carriers from 1.9 up to 4.5 Ton weight

The SB range of hydraulic breakers represent a unique concept in breaker technology with a patented, one-piece housing construction, the Solid Body concept. SB breakers have an outstanding power to weight ratio and are quick and easy to position. One piecing housing also means fewer components and less maintenance.



| rectifications | |
|--|----------------------------|
| Carrier Weight Class Service Weight | 4200 – 9900 lbs 310 lbs |
| Oil Flow | 6.5 - 12 GPM |
| Operating Pressure | 1450 - 2175 Psi |
| Impact Rate | 850 1900 blows/min |
| Working Tool Diameter | 1.97 Inch |
| Working Length of Tool | 9.85 Inch |
| Max Hydraulic Input Power | 11 kW |
| Sound Power Level Guaranteed | 114 dB(A) |
| Sound Pressure Level (r=10m) | 85 dB(A) |

Complete with hoses, bracket and chisel (or point). We will prepaid the freight and have someone install the bracket hoses and chisel.

Technical Specifications