

Engine

Emissions Tier (EPA)	Interim Tier 4
Engine Fuel	Diesel
Maximum Governed RPM	2,150 rpm
Horsepower	57 hp
Turbocharged Engine	<input type="checkbox"/>

Performance

Operating Weight	18,689 lb
Weight Class	8.4 t
Travel Speed - High	2.9 mph
Travel Speed - Low	1.8 mph
Arm Digging Force	7,659 lbf
Bucket Digging Force	12,280 lbf
Rated Lift Capacity	9325 lb
Lift Radius	118 in
Boom Swing - Left	70°
Boom Swing - Right	55°
Maximum Dig Depth	15.5 ft
Max Dump Height	16.7 ft
Maximum Reach at Ground Level	24.5 ft

Capacities

Fuel Tank	29.1 gal
-----------	----------

Hydraulic System

Auxiliary Std Flow	31.7 gal/ min
Auxiliary Pressure	3,046 psi

Dimension

Length	242.8 in
Overall Length in Travel Position	242.8 in
Width	90.6 in
Height	103.9 in
Height with Operator Cab	103.9 in

Features

Air Conditioning	<input checked="" type="checkbox"/>
Cab Enclosure	<input checked="" type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Heater Air Conditioning	<input checked="" type="checkbox"/>
Ratio	X
Tail Swing Type	Minimal
Engine Shutdown	<input type="checkbox"/>
Auxiliary Hydraulics	<input checked="" type="checkbox"/>
Secondary Auxiliary Hydraulics	X
Quick Tach System	X
Rubber Track	<input checked="" type="checkbox"/>
Selectable Auxiliary Hydraulic Flow	<input type="checkbox"/>
Angle Blade	<input type="checkbox"/>

Data supplied herein are based on engineering calculations and are not actual measurements. Specification(s) are provided for general sales purposes only and are subject to change without notice. Specification(s) for your individual job, plant or site may vary based on normal variations in design, manufacturing, operating conditions and other factors.