MB 750



Features & benefits

VibroSilenced Plus system
ContiLube II
AutoStart
Energy recovery
Percussion chamber ventilation

Applications

Demolition

Foundation work

Tunneling

Trenching

Underwater work

Boulder size reduction in quarries

MB Hydraulic Breakers for Carriers from 10 up to 17.0 Ton weight

Atlas Copco's range of medium-duty hydraulic breakers was developed for a wide variety of applications. The combined gas/oil power principle means they are both powerful and highly flexible with regard to oil flow rate and pressure. Their technically advanced percussion mechanism, e.g. with long piston stroke, reduce unavoidable vibrations far more efficiently than many other makes

Technical Specifications	
Carrier Weight Class	22,046 to 37,479 lbs
Service Weight	1654 lbs
Oil Flow	21.1 to 31.7 GPM
Operating Pressure	2030 to 2465 Psi
Impact Rate	370 to 840 blows/min
Working Tool Diameter	3.94 Inch
Working Length of Tool	21.65 Inch
Max Hydraulic Input Power	34 kW
Sound Power Level Guaranteed	117 dB(A)
Sound Pressure Level (r=10m)	88 dB(A)

Complete with hoses, bracket and chisel (or point). We will prepaid the freight and have someone install the bracket hoses and chisel.