

# Haugen

★ Work Platforms

★ Truss Jibs








877-580-6218



*Marv Haugen Enterprises Inc.*

*P.O. Box 868 • Casselton, ND 58012 • Phone: 701-347-4827 • Fax: 701-347-4830  
Website: [www.haugenattachments.com](http://www.haugenattachments.com) • E-mail: [haugen@equipitnow.com](mailto:haugen@equipitnow.com)*

## Features

-  Heavy duty steel mesh floor for years of dependability
-  Safety restraint tie down bar is standard on all Platforms
-  Industrial hinges and latches for strength and safety
-  Door Safety Pins allow the door to remain rigid and strong
-  Easily pins onto your machines  
Fork Tines
-  Safety pins secure side rails and doors
-  Meets and/or exceeds OSHA Standards



## Safety Features



**Safety Pins** are standard for all doors and side rails. Each pin is attached to the rail by a cable to prevent losing the safety pins



**Door Safety Pins** gives the door extra strength and allows the door to remain rigid at all times



**Safety Restraint Tie Downs** are standard on all platforms. This gives you a safe place to connect your safety harnesses



**Optional End Fork Slots** make it easy to transport your Platform. To be used for loading and unloading only



**Pins over your Fork Tines** Each pin is chained to the Platform. Fits to most Telehandlers



*Collapsible for easy transportation*

## SPECIFICATIONS

| Model Number | Size    | Capacity | Weight |
|--------------|---------|----------|--------|
| MWP-4x4      | 4x4     | 2000 LBS | 330    |
| MWP-4x6      | 4x6     | 2000 LBS | 390    |
| MWP-4x8      | 4x8     | 2000 LBS | 450    |
| MWP-4x116    | 4x 9'8" | 2000 LBS | 500    |
| MWP-4x10     | 4x10    | 2000 LBS | 510    |
| MWP-4x12     | 4x12    | 2000 LBS | 570    |

Custom sizes available upon request.

## Industrial Jibs

Fits on most types of Forklifts

Mounts to your Fork Tines



Manually adjusts from 6'9" to 12 feet  
with 9 different positions



| *Lift Capacity Rating |               |                    |
|-----------------------|---------------|--------------------|
| Jib Position          | Length        | *Max Lift Capacity |
| 1                     | 78.00 inches  | 6000 LBS           |
| 2                     | 86.00 inches  | 5715 LBS           |
| 3                     | 94.00 inches  | 5410 LBS           |
| 4                     | 102.00 inches | 5075 LBS           |
| 5                     | 110.25 inches | 4710 LBS           |
| 6                     | 118.50 inches | 4320 LBS           |
| 7                     | 126.75 inches | 3905 LBS           |
| 8                     | 135.00 inches | 3465 LBS           |
| 9                     | 143.25 inches | 3000 LBS           |

\* These lift capacity ratings are for the Industrial Jib only. The lifting capacity is ultimately determined by the host machine.

## Truss Jibs

- Quick Attach Truss Jibs for Telehandlers
- Custom built to fit your machine
- 2000 LBS lift capacity
- Available in 12 and 16 foot lengths



## Fork Slot Jibs

- Fork Slot Truss Jibs for Telehandlers, Fork Lifts, and Loaders
- 2000 LBS lift capacity
- Mounts to your fork tines
- Available in 12 and 16 foot lengths

