LGNG SR4039E ELECTRIC RT SCISSOR LIFT

 The large platform with high capacity maximizes productivity. ALEME

- Battery powered, zero emission and quiet drive mean this machine is environmentally friendly.
- Equipped with oscillating axles that provide excellent performance in soft and rough terrain conditions.
- Hydraulic outriggers deliver a better solution on uneven ground.
- Intelligent self-diagnostic system for quick troubleshooting.

SPECIFICATIONS


| MODELS | SR4069E (| SR1218E) |
|--|-------------------------|-----------|
| Measurements | Imperial | Metric |
| Work Height Max. | 45'7'' | 13.9m |
| A Platform Height - Raised | 39' | 11.9m |
| B Platform Height - Stowed | 5'1'' | 1.56m |
| Platform Length | 9'2'' | 2.79m |
| Platform Width | 5'3'' | 1.6m |
| Overall Length (with ladder) | 12'4'' | 3.76m |
| Overall Width | 5'10'' | 1.79m |
| Overall Height - Rails up | 8'10'' | 2.7m |
| Overall Height - Rails down | 6'8'' | 2.04m |
| Extension Deck | 5' | 1.52m |
| Wheelbase | 8' | 2.29m |
| Ground Clearance-Center | 9" | 0.23m |
| PRODUCTIVITY | | |
| Max. Platform Occupancy | 3(in) / 2(out) | |
| Platform Capacity | 805 lbs | 365kg |
| Platform Capacity - Extension | 310 lbs | 140kg |
| Drive Height | Full Height | |
| Gradeability - Stowed | 35% | |
| Min. Turning Radius | 15'7'' | 4.75m |
| Raise/Lower Speed | 61 / 55s | |
| Brakes | Rear-wheel brake | |
| Drive Mode | 4x2 | |
| Tires Type | Foam-filled Non-marking | |
| Tires Size | 26''x11'' | 663x283mm |
| POWER | | |
| Power Source | 48V DC 315Ah | |
| HYDRAULIC SYSTEM | | |
| Hydraulic Oil Volume | 18.5gal | 70L |
| WEIGHT | | |
| Machine Weight with Outriggers (CE/ANSI) | 11245 lbs | 5100kg |


STANDARD FEATURES


| Proportional control | Tilt alarm with lift cut-out |
|-----------------------|------------------------------------|
| Foldable guardrail | Overload sensing system |
| Emergency stop device | Descent alarm with flashing beacon |
| Manual brake release | All motions alarm |
| Emergency descent | Intelligent diagnostic system |
| Oscillating axle | Auto-leveling outriggers |
| Self-lock entry gate | Foam-filled non-marking tires |

OPTIONAL

| Telematics | Solid tires |
|-----------------------------|-------------------------|
| AC power to platform | Solid non-marking tires |
| Biodegradable hydraulic oil | Foam-filled tires |







Please contact LGMG or local dealer for more details.

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purpose only. This brochure comes into effect in May, 2023.

LINGONG HEAVY MACHINERY CO., LTD.

Address: No. 2676, Kejia Road, Jinan, Shandong, China Email: sales@lgmg.com.cn Tel: +86 531 6787 9283

LGMG Europe B.V.

Address: Donker Duyvisweg 301, 3316 BL Dordrecht, The Netherlands Email: sales@lgmgeurope.com Tel: +31 850 642 777

LGMG North America Inc.

Address: 4105 Live Oak Drive, Suite 100, The Colony, Texas 75056 United States Email: sales@lgmgna.com Tel: +1 833 288 5464

www.lgmglifts.com

