

INDIRECT FIRED HEATERS



FVO-400
Fuel Oil



FVNP-400
Dual Fuel – Natural Gas/ Propane

MODEL	FVO-400 Oil	FVNP-400 Dual Fuel
Heat Capacity	390,000 btuh	390,000 btuh
Fuel Tank Capacity	42 US gallons	External
Operating Time/ Fuel Consumption	14 hours 2.75 gal/hr	Propane - 4.26 GPH Natural Gas - 390 CFH
L x W x H	70"x 29"x 52"	70"x 29"x 47"
Heat Exchanger	16 gauge 304 Stainless Steel	16 gauge 304 Stainless Steel
Fan Motor	3/4 HP@1,725 rpm 2,500 CFM	3/4 HP@1,725 rpm 2,500 CFM
Ignition	Direct Spark Ignition	Direct Spark Ignition
Nozzle Size/ Gas Pressure	2.00 x 60B @ 170 PSI	Propane - 3.2" WC Natural Gas - 2.0" WC
Air Outlet (optional)	Two 12" diameter One 16" diameter	Two 12" diameter One 16" diameter
Wheels	Two 16" diameter Pneumatic Tubed Wheels	Two 16" diameter Pneumatic Tubed Wheels
Power Requirement	115V/60Hz/1Ph/15Amp	115V/60Hz/1Ph/15Amp
Approvals	cETLus	cETLus
Weight	450 lbs	365 lbs

DEPENDABLE HEAT WHEREVER YOU NEED IT

175° F outlet temperature rise
 Proven Riello burner technology
 Optional remote thermostat available
 ETL approved for use in the United States and Canada
 FVO-200 has a stackable frame for easy storage

