



Indirect Fired Heater

Part Number: FVNP-200RC

200,000 BTU Indirect Fired Dual Fuel Heater - Recirculating Hood

- Proven Riello burner technology
- Welded 304 stainless steel heat exchanger
- Powerful backward incline blower provides ultra-quiet operation & low amperage, ductable up to 150 ft
- Smart power indicator control verifies proper power supply to the heater
- Stackable frame allow for convenient transportation & storage

Specifications

NAME	DESCRIPTION
Heat Capacity	200,000 BTU/H
Fuel Consumption	Natural Gas- 190 CFH & Propane - 9.25 LBS/HR
Power Requirements	115V/15 AMPS (6AMP Draw)
Fan Motor/ Air Circulation	1/2 H.P. / 2,600 CFM
Heat Exchanger	16 Gauge 304 Stainless Steel
Ignition	Direct Spark
Gas Manifold Pressure	Propane - 1.45" WC / Natural Gas - 3.44" WC
Air Outlet	1 x 12" Dia or 1 X 16" Dia
Air Inlet	1 x 12" Dia
Wheels	2 x 12" Dia. Flat Free/ 2 x Casters
Dimensions / Weight	51.5" x 27" x 44" / 300 LBS.
Approvals	cETLus
Outlet Ducting	FV-HD12 - 12" x 12FT
Outlet Ducting:	FV-HDG16 - 16" x 25FT
Inlet Ducting	FV-HD12 - 12" x 12FT
Remote Thermostat	FV-THB