

INDIRECT FIRED HEATERS



FVO-400
Fuel Oil



FVNP-400
Dual Fuel – Natural Gas/ Propane

| MODEL | FVO-400 Oil | FVNP-400 Dual Fuel |
|-------------------------------------|--|---|
| Heat Capacity | 390,000 btuh | 390,000 btuh |
| Fuel Tank Capacity | 42 US gallons | External |
| Operating Time/ Fuel Consumption | 14 hours 2.75 gal/hr | Propane - 4.26 GPH Natural Gas - 390 CFH |
| L x W x H | 70"x 29"x 52" | 70"x 29"x 47" |
| Heat Exchanger | 16 gauge 304 Stainless Steel | 16 gauge 304 Stainless Steel |
| Fan Motor | 3/4 HP@1,725 rpm 2,500 CFM | 3/4 HP@1,725 rpm 2,500 CFM |
| Ignition | Direct Spark Ignition | Direct Spark Ignition |
| Nozzle Size/ Gas Pressure | 2.00 x 60B @ 170 PSI | Propane - 3.2" WC Natural Gas - 2.0" WC |
| Air Outlet (optional) | Two 12" diameter One 16" diameter | Two 12" diameter One 16" diameter |
| Wheels | Two 16" diameter Pneumatic Tubed Wheels | Two 16" diameter Pneumatic Tubed Wheels |
| Power Requirement | 115V/60Hz/1Ph/15Amp | 115V/60Hz/1Ph/15Amp |
| Approvals | cETLus | cETLus |
| Weight | 450 lbs | 365 lbs |

DEPENDABLE HEAT WHEREVER YOU NEED IT

175° F outlet temperature rise
 Proven Riello burner technology
 Optional remote thermostat available
 ETL approved for use in the United States and Canada
 FVO-200 has a stackable frame for easy storage

