





Standard Features:

- Fully Insulated Jacket
- Industrial Grade Burner
- Stainless Steel Heat Exchanger
- Satin Coated Steel w/ Powder Coated Paint
- Independent Fan & Blower
- Heavy Duty 6-Ply Pneumatic Tires
- Polarity & Running Lights
- Flexible Duct Attachment Pin Lock or Belt Cuff

- GenySis Primary Control w/ Diagnostic Reader (Oil)
- 42 US Gallon DW Fuel Tank w/ Gauge (Oil)
- 3 Trials For Ignition (LP/NG)
- EZ Ball-Valve Switch Over (LP/NG)
- Automatic High Limit Safety Switch-off
- Lifting Bail
- CSA/ETL Certified

pecifications:	IDF350 LP/NG (BLUE)	IDF350 -11 (RED)
- BTU/h	350,000	350,000
- Fuel Type	Propane/Natural Gas	Oil/Diesel/Kerosene
- CFM	2,500	2,500
- Fan Motor	1/2HP 1,800RPM	½HP 1,800RPM
- Static Pressure	.5"	.5"
- Flue Size	6"	6"
- Outlet Configuration	Dual 12" or Single 16"	Dual 12" or Single 16"
- Electrical Requirements	110-120V/15amp	110-120V/15amp
- Net Weight	420lbs	420lbs
- Dimensions (LxWxH)	70" x 35" x 52"	70" x 35" x 52"
- Crated Shipping Dimensions	83" x 37" x 52"	83" x 37" x 52"
- Crated Shipping Weight	580lbs	580lbs

Optional Considerations:

Remote Thermostat, Heat Recovery System, XLT Large 60 US Gallon Fuel Tank, Foam Filled Tires

WE. KNOW. HEAT.