



Indirect Fired Heater

Part Number: FVNP-400RC

390,000 BTU Indirect Fired Dual Fuel Heater - Recirculating Hood

- Proven Riello burner technology
- Welded 304 stainless steel heat exchanger
- Powerful backward incline blower provides ultra-quiet operation & low amperage, ductable up to 150 ft
- Smart power indicator control & volt meter help verify power supply

Specifications

NAME	DESCRIPTION
Heat Capacity	Up to 390,000 BTU/H
Fuel Consumption	Natural Gas - 380 CFH & Propane 18.5 LBS/HR
Power Requirements	115V/15 AMPS (10.5 AMP Draw)
Fan Motor/ Air Circulation	1 H.P. / 4000 CFM
Heat Exchanger	16 Gauge 304 Stainless Steel
Ignition	Direct Spark
Gas Pressure Manifold	Propane - 1.5" WC / Natural Gas - 2.0" WC
Air Outlet	2 x 12" Dia. or 1 X 16" Dia.
Air Inlet	1 x 16" Dia.
Wheels	2 x 16" Dia. Flat Free
Dimensions / Weight	70" x 29" x 47" / 365 LBS.
Approvals	cETLus
Outlet Ducting:	FV-HD12 - 12" x 12FT
Outlet Ducting:	FV-HDG16 - 16" x 25FT
Return Ducting:	FV-HDV16 - 16" x 12FT
Remote Thermostat:	FV-THB