


Specifications – Campo Blaze 700 (G = Propane, D = Diesel)



The Blaze 700, 800, 1000 & 2000

EMPOWERED BY INNOVATIVE ENGINEERING



Features

- ✓ Indirect-Fired
- ✓ The Blaze 700, 800, 1000 and 2000 are versatile High Performance Heaters
- ✓ Unique High Static Fan allows recirculation of warm inside air, resulting in fuel savings and even temperatures
- ✓ 400 ft of ducting can be used on the Blaze 1000
- ✓ Tempered Air Mode for LEED Construction allows for lower discharge temperatures when remote thermostat is satisfied in order to deliver continuous heat to the jobsite (Standard on Blaze 1000 and 2000, optional on Blaze 700 and 800)
- ✓ Variable fan control (3 speeds) provides flexibility in CFM delivery and heat rise, up to 200 F
- ✓ VFD Eliminates Large in-rush Current for Motor Starts
- ✓ 1PH 208-240V or 3PH 208V-240V Operation
- ✓ Optional "Plug and Play" burner kit can easily convert unit from diesel to NG or LP
- ✓ Available in three fuel options upon ordering: Natural Gas, Propane, or Diesel
- ✓ Ask about how our Heaters can help you with your next LEED construction project

High Performance Portable Heating

Efficient, Reliable, Safe & Easy to Service

NEW FEATURES FOR 2013 ON ALL 700 to 2000 MODELS:

- * PANEL MOUNT VOLTMETER PROVIDES POWER SUPPLY AND CONTROL VOLTAGE READINGS
- * GAS PRESSURE GAUGES ON INLET AND MANIFOLD SIDE OF TRAIN
- * NG/LP EASY SWITCHOVER VALVE ON TRAIN

Up to 16,000 CFM

4x more Static Pressure 6.5"

Unique High Static Fan

88% Efficiency

	BLAZE 700 G	*BLAZE 700 D
Input BTU's	700,000	700,000
Output BTU's	616,000	616,000
Beckett Gas Burner	CG10A	
Beckett Diesel Burner		CF800
Air Volume High (CFM)/1PH/3PH	10,000/16A /8.5A	10,000/16A /8.5A
Air Volume Medium (CFM)/1PH/3PH	8,500/14A /7.5A	8,500/14A /7.5A
Air Volume Low (CFM)/1PH/3PH	7,000/13A /7A	7,000/13A /7A
Temperature Rise High	140F	140F
Temperature Rise Medium	160F	160F
Temperature Rise Low	200F	200F
Ductability	200ft	200ft
Voltage (V)	(208V/240V)	(208V/240V)
Return Air Capability	YES	YES
Dimensions	5 92"x33.25"x45"	5 92"x33.25"x45"
Approx. Weight	1200lbs	1200lbs
Fuel	LP/NG	No.1/No.2