

# DUAL FUEL CONSTRUCTION HEATERS



**F-400T**



**F-1500T**

MODEL	F-400T	F-1000T	F-1500T
Fuel	Propane or Natural Gas	Propane or Natural Gas	Propane or Natural Gas
BTU/hr	400,000 btuh	1,000,000 btuh	1,500,000 btuh
Low Fire BTU/hr	N/A	N/A	650,000 btuh
Inlet Pressure			
Propane	11" W.C. MAX	11" W.C. MAX	11" W.C. MAX
Natural Gas	4.0" W.C. MIN	10" W.C. MIN	10" W.C. MIN
Power Requirement	115V/15Amp	115V/20Amp	115V/20Amp
Fan Motor	1/3 HP	1 HP	1 HP
Air Circulation	2,000 CFM	7,000 CFM	7,000 CFM
Ignition	Direct Spark Control	Direct Spark Control	Direct Spark Control
Thermostat Control	Yes	Yes	Yes
L x W x H	48" x 22" x 24"	61" x 29" x 38"	61" x 29" x 38"
Air Outlet	15" Diameter	26" Diameter	26" Diameter
Weight	90 lbs	356 lbs	360 lbs

## REQUIRED EQUIPMENT FOR HEATER INSTALLATIONS

Recommended For Model No.	Second Stage Regulator*	Typical Hose Assembly
F-400T	B42R0.75 (3/4" NPT)	S52180-12 3/4" x 15ft Hose Assembly
F-1000T	B42R1.25 (1-1/4" NPT)	S54180-20 1 1/4" x 15ft Hose Assembly
F-1500T	B31R1.25 (1-1/4" NPT)	S54180-20 1 1/4" x 15ft Hose Assembly

Note: \*Regulator sizing assumes job site inlet pressure of 2-10 PSI.

\*\*Custom hose assemblies are available upon request.



Ventless regulator available on request

